



OptiFlood MVP506

MVP506 CDM-T150W/942 OR GR ST

OptiFlood, MASTERColour CDM-T, 150 W, Open CT-POT

Philips has a long tradition of excellence in environmentally friendly asymmetric floodlighting systems for sports and general area lighting as well as architectural applications. OptiFlood's extremely efficient, best-in-class optical system provides an accurately controlled light distribution – total light cut-off above the horizontal and a peak beam intensity at high angles – keeping obtrusive light to a minimum. Both the MVP504 and MVP506 versions are available with two types of reflector asymmetric or road-lighting POT optics - for flexibility in application. They can also accommodate CosmoPolis metal-halide lamps for good color rendering, highpressure sodium lamps for economical operation, and MASTERColour CDM Elite MW lamps for highly efficient lighting with longer-lasting white light. OptiFlood is also available in a LED version (BVP506). With its compact shape and aesthetically pleasing design, OptiFlood can be used in applications where design and appearance are just important as technical performance. In the design, attention has also been focused on the detailing. This has led to integrated 'hidden' hinges, angle adjustment designed as part of the body and a mounting bracket angled to allow more aesthetic integration onto columns.

Product data

General Information	
Lamp family code	CDM-T [MASTERColour CDM-T]
Gear	CONV [Conventional]
Product family code	MVP506 [OptiFlood]
CE mark	Yes
ENEC mark	ENEC mark
Glow-wire test	Temperature 850 °C, duration 5 s

Light Technical	
Number of light sources	1
Light source color	942 neutral white
Optical cover type	Flat glass
Optic type outdoor	Open CT-POT
Operating and Electrical	
Input Voltage	230 V

Datasheet, 2023, April 29 data subject to change

OptiFlood MVP506

Power Consumption	150 W
Mechanical and Housing	
Housing Color	Gray
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK09 [10 J]
Protection class IEC	Safety class I
Product Data	
Order product name	MVP506 CDM-T150W/942 OR GR ST

Full product name	MVP506 CDM-T150W/942 OR GR ST
Full product code	871155972034000
Order code	72034000
Material Nr. (12NC)	910403043212
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711559720340
Numerator - Packs per outer box	1
EAN/UPC - Case	8711559720340

Dimensional drawing



