



LED Bollard II

BCP151 LED150/WW PSU 220-240V 9006

LED Low Power, 830 warm white, Power supply unit (On/Off), 220 to 240 V

People want to create a pleasant atmosphere around their property – something that will catch visitors’ attention, make them feel good and want to come back again. They would like to be able to create an appealing ambience with optimized-quality lighting at minimum cost. Combining reliable low-power LEDs and an integrated driver, the robustly designed LED Bollard II delivers an affordable LED lighting solution to meet your landscaping needs.

Product data

General Information		Color rendering index (CRI)		>80
Lamp family code	LED-LP [LED Low Power]	Number of light sources		1
Light source replaceable	No	Light source color		830 warm white
Number of gear units	1 unit	Optical cover type		Polycarbonate bowl/cover UV-resistant
Driver included	Yes			
Light source engine type	LED	Operating and Electrical		
Value ladder	Performance	Input Voltage		220 to 240 V
Embedded control	-	Line Frequency		50 to 60 Hz
CE mark	CE mark	Power Consumption		7 W
Warranty period	1 years	Power Factor (Fraction)		0.4
Flammability mark	For mounting on normally flammable surfaces	Connection		Screw connection block
		Cable		Cable without plug 3-pole
		Number of products on MCB of 16 A type B 1		
Light Technical		Temperature		
Luminous Flux	150 lm	Ambient temperature range		-20 to +40 °C
Correlated Color Temperature (Nom)	3000 K			
Luminous Efficacy (rated) (Nom)	21.43 lm/W			

LED Bollard II

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum extruded
Optical cover material	Polycarbonate
Housing Color	Aluminum and white
Mounting device	Baseplate
Optical cover finish	Matte
Overall height	800 mm
Overall diameter	180 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]

Protection class IEC	Safety class I
----------------------	----------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	BCP151 LED150/WW PSU 220-240V 9006
Full product name	BCP151 LED150/WW PSU 220-240V 9006
Full product code	910403308302
Order code	910403308302
Material Nr. (12NC)	910403308302
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163278940
Numerator - Packs per outer box	1
EAN/UPC - Case	8710163279343

Dimensional drawing

