



OptiFlood Mini MVP504

MVP504 CPO-TW90W K EB I

OptiFlood, MASTER CosmoWhite CPO-TW, 90 W, Electronic

Philips has a long tradition of excellence in environmentally friendly asymmetric floodlighting systems for sports and general area lighting as well as architectural applications. OptiFlood's extremely efficient, best-in-class optical system provides an accurately controlled light distribution – total light cut-off above the horizontal and a peak beam intensity at high angles – keeping obtrusive light to a minimum. Both the MVP504 and MVP506 versions are available with two types of reflector – asymmetric or road-lighting POT optics – for flexibility in application. They can also accommodate CosmoPolis metal-halide lamps for good color rendering, high-pressure sodium lamps for economical operation, and MASTERColour CDM Elite MW lamps for highly efficient lighting with longer-lasting white light. OptiFlood is also available in a LED version (BVP506). With its compact shape and aesthetically pleasing design, OptiFlood can be used in applications where design and appearance are just important as technical performance. In the design, attention has also been focused on the detailing. This has led to integrated 'hidden' hinges, angle adjustment designed as part of the body and a mounting bracket angled to allow more aesthetic integration onto columns.

Product data

General Information		Light Technical	
Lamp family code	CPO-TW [MASTER CosmoWhite CPO-TW]	ENEC mark	-
Gear	EB [Electronic]	Optical cover type	Clear glass
Product family code	MVP504 [OptiFlood]	Optic type outdoor	Optic for CosmoPolis lamp
Embedded control	-		
CE mark	Yes		

OptiFlood Mini MVP504

Operating and Electrical

Input Voltage	220 to 240 V
Power Consumption	90 W

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I

Product Data

Order product name	MVP504 CPO-TW90W K EB I
Full product name	MVP504 CPO-TW90W K EB I

Full EOC	872790029342500
Local code description	MVP504C90WEC
Order code	29342500
Material no. (12 NC)	910403766912
Local order code	MVP504C90WEC
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8727900293425
Numerator – packs per outer box	1
EAN/UPC – Case	8727900293425

Dimensional drawing

