

FWC LED

BWC110 LED9-/830 PSU II WH

SECURITY LED 110, LED Module 900 lm, Power supply unit (On/Off)

Only texts for Benelux market available

Product data

General Information	
Lamp family code	LED9 [LED Module 900 lm]
Light source replaceable	Yes
Number of gear units	Unit
Driver included	Yes
Photocell	-
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Light source engine type	LED
Product family code	BWC110 [SECURITY LED 110]
Lighting Technology	LED
Value ladder	Value
CE mark	Yes
Warranty period	5 years
Flammability mark	For mounting on normally flammable surfaces
ENEC mark	ENEC mark
Glow-wire test	Temperature 650 °C, duration 5 s
EU RoHS compliant	Yes

Light Technical	
Upwards light output ratio	0.08
Luminous Flux	900 lm
Standard tilt angle post-top	0°
Standard tilt angle side entry	0°
Correlated Colour Temperature	3000 K
Luminous efficacy (rated) (nom.)	100 lm/W
Colour rendering index (CRI)	>80
Number of light sources	1
Beam angle of light source	120 degree(s)
Light source colour	830 warm white
Optic type	-
Optical cover type	Opal bowl/cover
Luminaire light beam spread	180°
Optic type outdoor	Symmetrical

Operating and Electrical	
Input Voltage	200-220 V
Line Frequency	50 to 60 Hz
Inrush current	27 A
Inrush time	0.25 ms
Power Consumption	9 W

FWC LED

Power Factor (Fraction)	0.95
Connection	Screw connection block 3-pole
Cable	-
Number of products on MCB of 16 A type B	50

Temperature

Ambient temperature range	-40 to +50 °C

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing material	Acrylonitile styrene acrylate
Reflector material	-
Optic material	-
Optical cover/lens material	UV-stabilised polycarbonate cover
Fixation material	Polyamide
Housing Colour	White
Mounting device	Wall-mounting bracket
Optical cover/lens shape	Curved
Optical cover/lens finish	Opal
Overall length	242 mm
Overall width	242 mm
Overall height	136 mm
Effective projected area	0.04 m²
Dimensions (height x width x depth)	136 x 242 x 242 mm

Approval and Application

Ingress protection code	IP54 [Dust accumulation-protected, splash-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Philips standard surge-protection level
Sustainability rating	-
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM <3
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Driver failure rate at 5,000 hours	1 %
Lumen maintenance at median useful life* 50,000 h	L70


Application Conditions

Performance ambient temperature Tq	25 °C

Product Data

Order product name	BWC110 LED9-/830 PSU II WH
Full product name	BWC110 LED9-/830 PSU II WH
Full EOC	871829185189999
Order code	85189999
Material no. (12 NC)	910500454097
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8718291851899
Numerator – packs per outer box	4
EAN/UPC - Case	8718291851974

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2023, April 14 - data subject to change