



# EcoStyle

## ST440T LED39S/840 PSU MB WH

EcoStyle track mounting, LED Module, system flux 3500 lm, 840 neutral white, Power supply unit (On/Off), Medium beam, Safety class II, White

Retailers are looking for an affordable LED accent-lighting solution with a reasonable payback compared to conventional technologies. Now, thanks to EcoStyle, they need look no further. With a LED light source and dedicated reflector system, EcoStyle delivers powerful, good-quality accent lighting, enabling retailers to display their merchandise in the best possible light. For food and fashion retailers, EcoStyle is available with special light recipes to further enhance the store ambiance and to show the produce and goods on offer in the very best light: Fresh Food Champagne is the perfect LED solution for displaying fruit, vegetables, cheese, bread and pastries in a warm lighting ambiance; Fresh Food Meat creates the best light setting for meat enhancement in a cool natural ambiance; CrispWhite is the clear choice for fashion retailers to make colors appear rich and intense while keeping whites bright. The track-mounted EcoStyle is also available in a choice of black or white finish. And the combination of efficient LED technology and an innovative heatsink ensures that this is a reliable, lasting solution.

### Product data

| General Information      |   |   |                                  |
|--------------------------|---|---|----------------------------------|
| Lamp family code         | LED35S [LED Module, system flux 3500 lm]  | no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value. |                                  |
| Light source replaceable | No  |   |                                  |
| Number of gear units     | 1 unit  |   |                                  |
| Driver included          | Yes   | Service tag   | Yes                              |
| Remarks                  | *-Per Lighting Europe guidance paper  | Product family code   | ST440T [EcoStyle track mounting] |
|                          | "Evaluating performance of LED based luminaires - January 2018": statistically there is | Lighting Technology   | LED                              |
|                          |   | CE mark   | Yes                              |

|                   |   |
|-------------------|---|
| Warranty period   | 5 years                                     |
| Flammability mark | For mounting on normally flammable surfaces |
| ENEC mark         | ENEC mark                                   |
| Glow-wire test    | Temperature 650 °C, duration 5 s            |
| EU RoHS compliant | Yes   |

#### Light Technical

|                                    |                          |
|------------------------------------|--------------------------|
| Luminous Flux                      | 3,800 lm                 |
| Correlated Color Temperature (Nom) | 4000 K                   |
| Luminous Efficacy (rated) (Nom)    | 120.63492063492063 lm/W  |
| Color rendering index (CRI)        | 80                       |
| Number of light sources            | 1                        |
| Beam angle of light source         | 120 degree(s)            |
| Light source color                 | 840 neutral white        |
| Optic type                         | Medium beam              |
| Optical cover type                 | Acrylic bowl/cover clear |
| Luminaire light beam spread        | 22°                      |
| Unified glare rating CEN           | Not applicable           |

#### Operating and Electrical

|  |              |
|--|--------------|
| Input Voltage                            | 220 to 240 V |
| Line Frequency                           | 50 to 60 Hz  |
| Inrush current                           | 18 A         |
| Inrush time                              | 0.25 ms      |
| Power Consumption                        | 31.5 W       |
| Power Factor (Fraction)                  | 0.95         |
| Connection                               | -            |
| Cable                                    | -            |
| Number of products on MCB of 16 A type B | 34           |

#### Temperature

|                           |             |
|---------------------------|-------------|
| Ambient temperature range | 0 to +35 °C |
|---------------------------|-------------|

#### Controls and Dimming

|                               |                            |
|-------------------------------|----------------------------|
| Dimmable                      | No                         |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Constant light output         | No                         |

#### Mechanical and Housing

|                    |                               |
|--------------------|-------------------------------|
| Housing Material   | Polycarbonate                 |
| Reflector material | Polycarbonate aluminum coated |

|                                     |                         |
|-------------------------------------|-------------------------|
| Optic material                      | Polycarbonate           |
| Optical cover material              | Polymethyl methacrylate |
| Fixation material                   | Polyamide               |
| Housing Color                       | White                   |
| Optical cover finish                | Clear                   |
| Overall length                      | 230 mm                  |
| Overall width                       | 112 mm                  |
| Overall height                      | 194 mm                  |
| Dimensions (Height x Width x Depth) | 194 x 112 x 230 mm      |

#### Approval and Application

|                              |                         |
|------------------------------|-------------------------|
| Ingress protection code      | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard]   |
| Protection class IEC         | Safety class II         |

#### Initial Performance (IEC Compliant)

|                             |                      |
|-----------------------------|----------------------|
| Luminous flux tolerance     | +/-10%               |
| Initial chromaticity        | (0.38, 0.38) SDCM <5 |
| Power consumption tolerance | +/-10%               |

#### Over Time Performance (IEC Compliant)

|   |     |
|---|-----|
| Control gear failure rate at median useful life 50000 h | 5 % |
| Lumen maintenance at median useful life* 50000 h        | L80 |

#### Application Conditions

|                                    |       |
|------------------------------------|-------|
| Performance ambient temperature Tq | 25 °C |
| Suitable for random switching      | No    |

#### Product Data

|                                 |                             |
|---------------------------------|-----------------------------|
| Order product name              | ST440T LED39S/840 PSU MB WH |
| Full product name               | ST440T LED39S/840 PSU MB WH |
| Full product code               | 871869625935100             |
| Order code                      | 910500456866                |
| Material Nr. (12NC)             | 910500456866                |
| Numerator - Quantity Per Pack   | 1                           |
| EAN/UPC - Product/Case          | 8718696259351               |
| Numerator - Packs per outer box | 1                           |
| EAN/UPC - Case                  | 8718696259351               |

## Dimensional drawing

