



LuxSpace Accent CrispWhite

RS741B LED27S/CRW PSE-E MB WH

LuxSpace Accent Compact G3, LED Module, system flux 2700 lm, Crisp white, Power supply unit DC compatible, external, Medium beam, White

Retailers are increasingly having to contend with rising energy prices. At the same time, they need to retain high-quality lighting to catch the customer's eye, as well as flexibility in architectural integration. Fashion retailers generally want superior light sources that illuminate fabrics in the truest way possible, making colors appear rich and intense while keeping whites bright. A warm color temperature is often preferred, as it keeps colors true and saturated. Until now, a drawback of LED has been that whites can appear yellowish. The good news – that's about to change. CrispWhite is a unique concept in retail lighting that makes whites appear whiter than white, yet still gives colors a warm and saturated intensity. This new color experience will wow customers and make merchandise impossible to resist.

Product data

General Information			
Lamp family code	LED27S [LED Module, system flux 2700 lm]	B10. Therefore, the median useful life (B50) value also represents the B10 value.	
Light source replaceable	No	Service tag	Yes
Number of gear units	1 unit	Product family code	RS741B [LuxSpace Accent Compact G3]
Driver included	Yes	Lighting Technology	LED
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example	CE mark	Yes
		Warranty period	5 years
		Flammability mark	For mounting on normally flammable surfaces
		ENEC mark	ENEC mark

LuxSpace Accent CrispWhite

Glow-wire test	Temperature 650 °C, duration 5 s
EU RoHS compliant	Yes

Light Technical

Luminous Flux	2,700 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	67.5 lm/W
Color rendering index (CRI)	≥95
Number of light sources	1
Beam angle of light source	120 degree(s)
Light source color	Crisp white
Optic type	Medium beam
Optical cover type	-
Luminaire light beam spread	30°

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	- W W
Average CLO power consumption	- W W
Inrush current	14.5 A
Inrush time	0.22 ms
Power Consumption	40 W
Power Factor (Fraction)	0.9
Connection	Push-in connector and pull relief
Cable	-
Number of products on MCB of 16 A type B	32

Temperature

Ambient temperature range	+10 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit DC compatible, external
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	Polycarbonate aluminum coated

Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover finish	Clear
Overall height	126 mm
Overall diameter	130 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.39) SDCM <3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L80

Application Conditions

Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes

Product Data

Order product name	RS741B LED27S/CRW PSE-E MB WH
Full product name	RS741B LED27S/CRW PSE-E MB WH
Full product code	871869626381500
Order code	910500457113
Material Nr. (12NC)	910500457113
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696263815
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696263815

LuxSpace Accent CrispWhite

Dimensional drawing

