



StoreFlux gen3 rim

GD601B LED20S/830 PSU-E NB WH-WH

StoreFlux3, LED Module, system flux 2000 lm, 830 warm white, Power supply unit external (On/Off), Narrow beam, White and white

With StoreFlux, retailers can enjoy the superior quality of light and market-leading energy efficiency of PerfectAccent optics in a refined and neutral product design that nicely blends in-shop architecture. The StoreFlux gridlight can be equipped with up to three LED modules with the PerfectAccent reflector system to deliver top-quality accent lighting that makes your shop and merchandise look great. As well as its long service lifetime, StoreFlux also offers tool-free reflector replacement, with an easy access to the driver for hassle-free maintenance.

Warnings and Safety

- The luminaire should be mounted out of arm's reach. Manipulating the product when hot is only possible with an insulated glove
- The luminaire should be installed and disassembled by a qualified electrician and wired in accordance with the latest IEE electrical regulations or the national requirements
- All photometrical data is calculated without optional front glass. Flux should be reduced by 3.5% when using a front glass
- In case of no front glass lens, cleaning the optic should only be done with pressurised air. Touching the LED or reflector is forbidden. For areas with high levels of dust, the use of the optional front glass is strongly advised, as it can then be easily cleaned with a (dry) microfibre cloth
- For multi-spot configurations, please use single configuration photometry and duplicate it according to the number of spots in a given configuration.

Product data

| General Information | | Driver included | Yes |
|--------------------------|--|-----------------|---|
| Lamp family code | LED20S [LED Module, system flux 2000 lm] | Remarks | *- According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there |
| Light source replaceable | No | | |
| Number of gear units | Unit | | |

StoreFlux gen3 rim

| | |
|---------------------|--|
| | is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median useful life (B50) value also represents the B10 value. |
| Product family code | GD601B [StoreFlux3] |
| Lighting Technology | LED |
| Value ladder | Specification |
| CE mark | Yes |
| Warranty period | 5 years |
| Flammability mark | For mounting on normally flammable surfaces |
| ENEC mark | ENEC mark |
| Glow-wire test | Temperature 650 °C, duration 5 s |
| EU RoHS compliant | Yes |

Light Technical

| | |
|----------------------------------|------------------------|
| Luminous Flux | 2,000 lm |
| Correlated Colour Temperature | 3000 K |
| Luminous efficacy (rated) (nom.) | 102.0408163265306 lm/W |
| Colour rendering index (CRI) | ≥80 |
| Beam angle of light source | 120 degree(s) |
| Light source colour | 830 warm white |
| Optic type | Narrow beam |
| Optical cover type | Clear glass |
| Luminaire light beam spread | 10° |
| Unified Glare Rating (CEN) | Not applicable |

Operating and Electrical

| | |
|--|-----------------------------------|
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 to 60 Hz |
| Inrush current | 6.1 A |
| Inrush time | 0.31 ms |
| Power Consumption | 19.6 W |
| Power Factor (Fraction) | 0.9 |
| Connection | Push-in connector and pull relief |
| Cable | - |
| Number of products on MCB of 16 A type B | 34 |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | +10 to +40 °C |
|---------------------------|---------------|

Controls and Dimming

| | |
|-------------------------------|-------------------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit external (On/Off) |
| Control interface | - |
| Constant light output | No |

Mechanical and Housing

| | |
|-------------------------------------|--------------------|
| Housing material | Steel |
| Reflector material | Polycarbonate |
| Optic material | Polycarbonate |
| Optical cover/lens material | Glass |
| Fixation material | Steel |
| Housing Colour | White and white |
| Optical cover/lens finish | Clear |
| Overall length | 179 mm |
| Overall width | 179 mm |
| Overall height | 165 mm |
| Dimensions (height x width x depth) | 165 x 179 x 179 mm |

Approval and Application

| | |
|------------------------------|-------------------------|
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| Protection class IEC | Safety class II |

Initial Performance (IEC Compliant)

| | |
|-----------------------------|----------------------|
| Luminous flux tolerance | +/-10% |
| Initial chromaticity | (0.43, 0.40) SDCM <3 |
| Power consumption tolerance | +/-10% |

Over Time Performance (IEC Compliant)

| | |
|--|-----|
| Control gear failure rate at median useful life 50,000 h | 5 % |
| Lumen maintenance at median useful life* 50,000 h | L80 |

Application Conditions

| | |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C |
| Maximum dim level | Not applicable |
| Suitable for random switching | No |

Product Data

| | |
|-----------------------------------|----------------------------------|
| Order product name | GD601B LED20S/830 PSU-E NB WH-WH |
| Full product name | GD601B LED20S/830 PSU-E NB WH-WH |
| Full EOC | 871869688421800 |
| Order code | 88421800 |
| Material no. (12 NC) | 910500458292 |
| SAP numerator – quantity per pack | 1 |
| EAN/UPC — Product/Case | 8718696884218 |
| Numerator – packs per outer box | 1 |
| EAN/UPC – Case | 8718696884218 |

StoreFlux gen3 rim

Dimensional drawing

