



# LuxSpace Accent Fresh Food

### RS751B LED19S/ROSE PSE-E WB WH LIN

LuxSpace Accent Fresh Food, 22.5 W, 1900 lm, 2200 K, Wide beam. White

Retailers are increasingly having to contend with rising energy prices. At the same time, they need to retain high-quality lighting to catch the customer's eye, as well as flexibility in architectural integration. Food retailers generally want superior light sources that illuminate their fresh food counters in the freshest way possible, making food appealing while keeping the light ambiance attractive and welcoming. When a warm light ambiance is preferred, Fresh Food Champagne is the perfect LED solution to light fruit, vegetables, cheese, bread and pastries. Fresh Food Rose is a perfect warm-light solution for meat counters, enhancing the redness of meat but also slowing down the discoloration of sliced meat. When a brighter or more natural light ambiance is preferred, Fresh Food Authentic White is recommended for fruits, vegetables, cheeses, bread and pastries. Fresh Food Meat creates the best light setting for meat enhancement in a cooler ambiance.

#### **Product data**

LED19S [LED module, system flux 1900 lm]
No
Unit
Yes
*- According to the Lighting Europe guidance
paper 'Evaluating performance of LED based
luminaires – January 2018': statistically there
is no relevant difference in lumen

	maintenance between the B50 and, for
	example, the B10. Therefore, the median
	useful life (B50) value also represents the B10
	value.
Product family code	RS751B [LuxSpace Accent Performance G3]
Lighting Technology	LED
Value ladder	Specification
CE mark	Yes
Warranty period	5 years

Datasheet, 2023, April 29 data subject to change

## **LuxSpace Accent Fresh Food**

Flammability mark	For mounting on normally flammable
	surfaces
ENEC mark	ENEC mark
Glow-wire test	Temperature 650 °C, duration 5 s
EU RoHS compliant	Yes
Light Technical	
Luminous Flux	1,900 lm
Correlated Colour Temperature	2200 K
Luminous efficacy (rated) (nom.)	84 lm/W
	≥80
Colour rendering index (CRI)  Beam angle of light source	
Light source colour	120 degree(s)  Rosé
	Wide beam
Optical cover type	
Optical cover type	Linear-lens array oval shape
Luminaire light beam spread	30° x 60°
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	32 A
Inrush time	0.25 ms
Power Consumption	22.5 W
Power Factor (Fraction)	0.9
Connection	Push-in connector and pull relief
Cable	-
Number of products on MCB of 16 A type	12
В	
Temperature	
Ambient temperature range	+10 to +40 °C
Ambient temperature range	10 10 140 C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit DC-compatible, external
Control interface	-
Constant light output	No

Aluminium

Housing material

Reflector material	Aluminium
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Colour	White
Optical cover/lens finish	Frosted
Overall height	150 mm
Overall diameter	168 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.48, 0.38)
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compl	iant)
Control gear failure rate at median useful	5 %
Control gear failure rate at median useful life 50,000 h	5 %
•	5 % L80
life 50,000 h	
life 50,000 h  Lumen maintenance at median useful	
life 50,000 h  Lumen maintenance at median useful	
life 50,000 h  Lumen maintenance at median useful life* 50,000 h	
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions	L80
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq	L80 25 °C
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq	L80 25 °C
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching	L80 25 °C
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data	L80  25 °C  Yes
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name	L80  25 °C  Yes  RS751B LED19S/ROSE PSE-E WB WH LIN
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name	L80  25 °C  Yes  RS751B LED19S/ROSE PSE-E WB WH LIN  RS751B LED19S/ROSE PSE-E WB WH LIN
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full EOC	L80  25 °C  Yes  RS751B LED19S/ROSE PSE-E WB WH LIN RS751B LED19S/ROSE PSE-E WB WH LIN 871869916747900
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full EOC  Order code	L80  25 °C  Yes  RS751B LED19S/ROSE PSE-E WB WH LIN  RS751B LED19S/ROSE PSE-E WB WH LIN  871869916747900  16747900
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full EOC  Order code  Material no. (12 NC)	L80  25 °C  Yes  RS751B LED19S/ROSE PSE-E WB WH LIN RS751B LED19S/ROSE PSE-E WB WH LIN 871869916747900 16747900 910500459458
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full EOC  Order code  Material no. (12 NC)  SAP numerator – quantity per pack	L80  25 °C  Yes  RS751B LED19S/ROSE PSE-E WB WH LIN RS751B LED19S/ROSE PSE-E WB WH LIN 871869916747900  16747900  910500459458  1
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full EOC  Order code  Material no. (12 NC)  SAP numerator – quantity per pack  EAN/UPC — Product/Case	L80  25 °C  Yes  RS751B LED19S/ROSE PSE-E WB WH LIN  RS751B LED19S/ROSE PSE-E WB WH LIN  871869916747900  910500459458  1  8718699167479
life 50,000 h  Lumen maintenance at median useful life* 50,000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full EOC  Order code  Material no. (12 NC)  SAP numerator – quantity per pack  EAN/UPC — Product/Case  Numerator – packs per outer box	L80  25 °C  Yes  RS751B LED19S/ROSE PSE-E WB WH LIN RS751B LED19S/ROSE PSE-E WB WH LIN 871869916747900 16747900 910500459458 1 8718699167479 1

## **LuxSpace Accent Fresh Food**

#### Dimensional drawing











