



# LuxSpace Accent Fresh Food

## RS752B LED19S/ROSE PSE-E WB WH

LuxSpace Accent Fresh Food, 22.5 W, 1900 lm, 2200 K, Wide beam. White

Retailers are increasingly having to contend with rising energy prices. At the same time, they need to retain high-quality lighting to catch the customer's eye, as well as flexibility in architectural integration. Food retailers generally want superior light sources that illuminate their fresh food counters in the freshest way possible, making food appealing while keeping the light ambiance attractive and welcoming. When a warm light ambiance is preferred, Fresh Food Champagne is the perfect LED solution to light fruit, vegetables, cheese, bread and pastries. Fresh Food Rose is a perfect warm-light solution for meat counters, enhancing the redness of meat but also slowing down the discoloration of sliced meat. When a brighter or more natural light ambiance is preferred, Fresh Food Authentic White is recommended for fruits, vegetables, cheeses, bread and pastries. Fresh Food Meat creates the best light setting for meat enhancement in a cooler ambiance.

#### **Product data**

General Information	
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Remarks	*-Per Lighting Europe guidance paper
	"Evaluating performance of LED based
	luminaires - January 2018": statistically
	there is no relevant difference in lumen
	maintenance between B50 and for example

	B10. Therefore, the median useful life (B50)
	value also represents the B10 value.
Product family code	RS752B [LuxSpace Accent Performance G3]
Lighting Technology	LED
Value ladder	Specification
CE mark	Yes
Warranty period	5 years
Flammability mark	For mounting on normally flammable
	surfaces

Datasheet, 2023, May 1 data subject to change

# **LuxSpace Accent Fresh Food**

ENEC mark	ENEC mark	Optical cover material	Poly
Glow-wire test	Temperature 650 °C, duration 5 s	Fixation material	-
EU RoHS compliant	Yes	Housing Color	Whit
		Optical cover finish	Frost
Light Technical		Overall length	231 n
Luminous Flux	1,900 lm	Overall width	168 r
Correlated Color Temperature (Nom)	2200 K	Overall height	126 n
Luminous Efficacy (rated) (Nom)	84 lm/W	Overall diameter	168 r
Color rendering index (CRI)	≥80	Dimensions (Height x Width x Depth)	126 x
Number of light sources	1		
Beam angle of light source	120 degree(s)	Approval and Application	
Light source color	Rosé	Ingress protection code	IP20
Optic type	Wide beam	Mech. impact protection code	IK02
Optical cover type	-	Sustainability rating	-
Luminaire light beam spread	41°	Protection class IEC	Safe
Operating and Electrical		Initial Performance (IEC Compliant)	
Input Voltage	220 to 240 V	Luminous flux tolerance	+/-10
Line Frequency	50 to 60 Hz	Initial chromaticity	(0.48
Initial CLO power consumption	- W	Power consumption tolerance	+/-10
Average CLO power consumption	- W		
Inrush current	32 A	Over Time Performance (IEC Compli	ant)
Inrush time	0.25 ms	Control gear failure rate at median useful	5 %
Power Consumption	22.5 W	life 50000 h	
Power Factor (Fraction)	0.9	Lumen maintenance at median useful life*	L80
Connection	Push-in connector and pull relief	50000 h	
Cable	-		
Number of products on MCB of 16 A type	12	Application Conditions	
В		Performance ambient temperature Tq	25 °C
		Suitable for random switching	Yes
Temperature			
Ambient temperature range	+10 to +40 °C	Product Data	
		Order product name	RS75
Controls and Dimming		Full product name	RS75
Dimmable	No	Full product code	8718
Driver/power unit/transformer	Power supply unit DC compatible, external	Order code	1674
Control interface	-	Material Nr. (12NC)	9105
Constant light output	No	Numerator - Quantity Per Pack	1
		EAN/UPC - Product/Case	8718
Mechanical and Housing		Numerator - Packs per outer box	1
Housing Material	Aluminum	EAN/UPC - Case	8718
Reflector material	Aluminum		
Optic material	Polycarbonate		

Optical cover material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover finish	Frosted
Overall length	231 mm
Overall width	168 mm
Overall height	126 mm
Overall diameter	168 mm
Dimensions (Height x Width x Depth)	126 x 168 x 231 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.48, 0.38)
Power consumption tolerance	+/-10%
Over Time Performance (IEC Complia	unt)
Control gear failure rate at median useful	F 0/
Control gear failure rate at median userut	5 %
life 50000 h	5 %
life 50000 h	
life 50000 h Lumen maintenance at median useful life* 50000 h	
life 50000 h  Lumen maintenance at median useful life*	
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq	L80 25 ℃
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions	L80
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching	L80 25 ℃
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data	L80  25 °C  Yes
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching	L80  25 °C  Yes  RS752B LED19S/ROSE PSE-E WB WH
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name	L80  25 °C  Yes  RS752B LED19S/ROSE PSE-E WB WH  RS752B LED19S/ROSE PSE-E WB WH
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full product code	L80  25 °C  Yes  RS752B LED19S/ROSE PSE-E WB WH RS752B LED19S/ROSE PSE-E WB WH 871869916749300
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full product code  Order code	25 °C Yes  RS752B LED19S/ROSE PSE-E WB WH RS752B LED19S/ROSE PSE-E WB WH 871869916749300 16749300
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full product code	L80  25 °C  Yes  RS752B LED19S/ROSE PSE-E WB WH RS752B LED19S/ROSE PSE-E WB WH 871869916749300
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full product code  Order code	25 °C Yes  RS752B LED19S/ROSE PSE-E WB WH RS752B LED19S/ROSE PSE-E WB WH 871869916749300 16749300
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full product code  Order code  Material Nr. (12NC)	L80  25 °C  Yes  RS752B LED19S/ROSE PSE-E WB WH RS752B LED19S/ROSE PSE-E WB WH 871869916749300  16749300  910500459460
life 50000 h  Lumen maintenance at median useful life* 50000 h  Application Conditions  Performance ambient temperature Tq  Suitable for random switching  Product Data  Order product name  Full product name  Full product code  Order code  Material Nr. (12NC)  Numerator - Quantity Per Pack	L80  25 °C  Yes  RS752B LED19S/ROSE PSE-E WB WH RS752B LED19S/ROSE PSE-E WB WH 871869916749300 16749300 910500459460 1

## **LuxSpace Accent Fresh Food**

### Dimensional drawing











