PHILIPS Lighting



LuxSpace Accent Fresh Food

RS752B LED27S/ROSE PSE-E VWB WH

LuxSpace Accent Fresh Food, 32.5 W, 2700 lm, 2200 K, Very wide beam, White

Retailers are increasingly having to contend with rising energy prices. At the same time, they need to retain high-quality lighting to catch the customer's eye, as well as flexibility in architectural integration. Food retailers generally want superior light sources that illuminate their fresh food counters in the freshest way possible, making food appealing while keeping the light ambiance attractive and welcoming. When a warm light ambiance is preferred, Fresh Food Champagne is the perfect LED solution to light fruit, vegetables, cheese, bread and pastries. Fresh Food Rose is a perfect warm-light solution for meat counters, enhancing the redness of meat but also slowing down the discoloration of sliced meat. When a brighter or more natural light ambiance is preferred, Fresh Food Authentic White is recommended for fruits, vegetables, cheeses, bread and pastries. Fresh Food Meat creates the best light setting for meat enhancement in a cooler ambiance.

Product data

General Information

Light source replaceable	No
Number of gear units	Unit
Driver included	Yes
Remarks	*- According to the Lighting Europe
	guidance paper 'Evaluating performance of
	LED based luminaires – January 2018':
	statistically there is no relevant difference in
	lumen maintenance between the B50 and,

	for example, the B10. Therefore, the median
	useful life (B50) value also represents the
	B10 value.
Product family code	RS752B [LuxSpace Accent Performance G3]
Lighting Technology	LED
Value ladder	Specification
CE mark	Yes
Warranty period	5 years


LuxSpace Accent Fresh Food


Flammability mark	
Flammability mark	For mounting on normally flammable
ENEC mark	surfaces ENEC mark
Glow-wire test	Temperature 650 °C, duration 5 s
EU RoHS compliant	Yes
Light Technical	
	2,700 las
Luminous Flux	2,700 lm
Correlated Colour Temperature	2200 K
Luminous efficacy (rated) (nom.)	83 lm/W
Colour rendering index (CRI)	280
Beam angle of light source	120 degree(s)
Light source colour	Rosé
Optic type	Very wide beam
Optical cover type	-
Luminaire light beam spread	54°
On surveying and Else to be d	
Operating and Electrical	220 - 240 -
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	32 A
Inrush time	0.25 ms
Power Consumption	32.5 W
Power Factor (Fraction)	0.9
Connection	Push-in connector and pull relief
Cable	-
Number of products on MCB of 16 A type	12
В	
Temperature	
Ambient temperature range	+10 to +40 °C
Controls and Dimming	
Controls and Dimming	No
Dimmable	No
Driver/power unit/transformer	Power supply unit DC-compatible, external
Control interface	-
Constant light output	No
Machanical and Develop	
Mechanical and Housing	
Housing material	Aluminium
Reflector material	Aluminium
Optic material	Polycarbonate

Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Colour	White
Optical cover/lens finish	Frosted
Overall length	231 mm
Overall width	168 mm
Overall height	126 mm
Overall diameter	168 mm
Dimensions (height x width x depth)	126 x 168 x 231 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.48, 0.38)
Power consumption tolerance	+/-10%
Over Time Performance (IEC Complia	nt)
Over Time Performance (IEC Complia Control gear failure rate at median useful	
Over Time Performance (IEC Complia	nt) 5 %
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h	nt) 5 %
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life*	nt) 5 %
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life*	nt) 5 %
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h	nt) 5 %
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions	nt) 5 % L80
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq	nt) 5 % L80 25 °C
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data	nt) 5 % L80 25 ℃ Yes
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data Order product name	nt) 5 % L80 25 °C Yes RS752B LED27S/ROSE PSE-E VWB WH
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data	nt) 5 % L80 25 °C Yes RS752B LED27S/ROSE PSE-E VWB WH
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data Order product name	nt) 5 % L80 25 ℃ Yes
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data Order product name Full product name	nt) 5 % L80 25 °C Yes RS752B LED27S/ROSE PSE-E VWB WH RS752B LED27S/ROSE PSE-E VWB WH
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data Order product name Full product name Full EOC	nt) 5 % L80 25 °C Yes RS752B LED27S/ROSE PSE-E VWB WH RS752B LED27S/ROSE PSE-E VWB WH 871869916751600
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data Order product name Full product name Full EOC Order code	nt) 5 % L80 25 °C Yes RS752B LED27S/ROSE PSE-E VWB WH RS752B LED27S/ROSE PSE-E VWB WH 871869916751600 16751600
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data Order product name Full product name Full EOC Order code Material no. (12 NC)	nt) 5 % L80 25 °C Yes RS752B LED27S/ROSE PSE-E VWB WH RS752B LED27S/ROSE PSE-E VWB WH 871869916751600 16751600 910500459462
Over Time Performance (IEC Complia Control gear failure rate at median useful life 50,000 h Lumen maintenance at median useful life* 50,000 h Application Conditions Performance ambient temperature Tq Suitable for random switching Product Data Order product name Full product name Full product name Full EOC Order code Material no. (12 NC) SAP numerator – quantity per pack	nt) 5 % L80 25 °C Yes RS752B LED27S/ROSE PSE-E VWB WH RS752B LED27S/ROSE PSE-E VWB WH 871869916751600 16751600 910500459462 1

LuxSpace Accent Fresh Food

Dimensional drawing







© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 29 - data subject to change