# **PHILIPS** Lighting



# **ArenaVision MVF404**

# MVF404 MHN-SEH2000W/956 B5 SI

ARENAVISION, MASTER MHN-SE High Output, 2000 W, Beam category B5

The ArenaVision MVF404 floodlight – designed for outdoor sports stadiums – dramatically increases the theatrical and emotional impact of sports for TV audiences and spectators, while allowing the players to perform under optimal visual conditions. Thanks to the innovative Philips MHN-SE 2000 W high-output compact single-ended metal-halide lamp and high-tech single-piece precision optics, ArenaVision MVF404 offers much higher optical efficiency than ever before. In addition, this 2 kW floodlight boasts easy lamp fitting and replacement, full IP65 compliance, safety knife connector system and a breakthrough electronic hotrestrike solution – while continuing to deliver all the traditional benefits of Philips ArenaVision systems. The (optional) flicker-free version of ArenaVision MVF404 is designed to ensure that the flicker effect is fully eliminated in order to guarantee perfect images filmed with super-slow-motion cameras at sports events. The flickerfree version of ArenaVision MVF404 comes equipped with a special electronic igniter, which works in combination with Philips' electronic-ballast GearUnits (ECM330), to be ordered separately.

#### **Product data**

General Information	
Lamp family code	MHN-SEH [MASTER MHN-SE High Output]
Number of gear units	-
Gear	-
Product family code	MVF404 [ARENAVISION]
Value ladder	Specification
CE mark	Yes
Warranty period	1 years
Flammability mark	-


ENEC mark	ENEC mark
EU RoHS compliant	Yes
Light Technical	
Standard tilt angle posttop	-
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	5600 K
Color rendering index (CRI)	>90
Number of light sources	1

## ArenaVision MVF404

Light source color	956 daylight	Optical cover finish	-
Optical cover type	Front-glass downlighting version	Overall height	535 mm
Luminaire light beam spread	-	Effective projected area	0.2 m²
Optic type outdoor	Beam category B5		
		Approval and Application	
Operating and Electrical		Ingress protection code	IP65 [Dust penetration-protected, jet-proof
Input Voltage	380 to 415 V	Mech. impact protection code	IK08 [5 J vandal-protected]
Line Frequency	50 to 60 Hz	Surge Protection (Common/Differential)	-
Power Consumption	2,000 W	Sustainability rating	-
Connection	Screw connector	Protection class IEC	Safety class I
Cable	-		
		Application Conditions	
Temperature		Maximum dim level	Not applicable
Ambient temperature range	-30 to +35 °C		
		Product Data	
Controls and Dimming		Order product name	MVF404 MHN-SEH2000W/956 B5 SI
Dimmable	No	Full product name	MVF404 MHN-SEH2000W/956 B5 SI
Constant light output	No	Full product code	872790050204600
		Order code	910502218518
Mechanical and Housing		Material Nr. (12NC)	910502218518
Housing Material	Aluminum	Local order code	9105-022-18518
Reflector material	Aluminum	Numerator - Quantity Per Pack	1
Optic material	Aluminum	EAN/UPC - Product/Case	8727900502046
Optical cover material	-	Numerator - Packs per outer box	1
Fixation material	Steel	EAN/UPC - Case	8727900502046
Housing Color	Aluminum		
Mounting device	Mounting bracket adjustable		

### Dimensional drawing

Optical cover shape



\_

**ArenaVision MVF404** 



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 16 - data subject to change