PHILIPS Lighting



ArenaVision MVF404

MVF404 MHN-SEH2000W/956 380-415V B3 SI A

ARENAVISION, MASTER MHN-SE High Output, 2000 W, Beam category B3

The ArenaVision MVF404 floodlight – designed for outdoor sports stadiums – dramatically increases the theatrical and emotional impact of sports for TV audiences and spectators, while allowing the players to perform under optimal visual conditions. Thanks to the innovative Philips MHN-SE 2000 W high-output compact single-ended metal-halide lamp and high-tech single-piece precision optics, ArenaVision MVF404 offers much higher optical efficiency than ever before. In addition, this 2 kW floodlight boasts easy lamp fitting and replacement, full IP65 compliance, safety knife connector system and a breakthrough electronic hotrestrike solution – while continuing to deliver all the traditional benefits of Philips ArenaVision systems. The (optional) flicker-free version of ArenaVision MVF404 is designed to ensure that the flicker effect is fully eliminated in order to guarantee perfect images filmed with super-slow-motion cameras at sports events. The flickerfree version of ArenaVision MVF404 comes equipped with a special electronic ignitor, which works in combination with Philips' flicker-free electronic-ballast GearUnits (ECM330), to be ordered separately.

Product data


Lamp family code Number of gear units Gear	MHN-SEH [MASTER MHN-SE High Output]	
-	-	
Gear	-	
	-	
Product family code	MVF404 [ARENAVISION]	
Value ladder	Specification	
CE mark	Yes	
Warranty period	1 years	
Flammability mark		

ENEC mark	ENEC mark
EU RoHS compliant	Yes
Light Technical	
Standard tilt angle posttop	-
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	5600 K
Color rendering index (CRI)	>90
Number of light sources	1

ArenaVision MVF404

Light source color	956 daylight	Optical cover finish	-
Optical cover type	Front-glass downlighting version	Overall height	535 mm
Luminaire light beam spread	-	Effective projected area	0.2 m²
Optic type outdoor	Beam category B3		
		Approval and Application	
Operating and Electrical		Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Input Voltage	380 to 415 V	Mech. impact protection code	IK08 [5 J vandal-protected]
Line Frequency	50 to 60 Hz	Surge Protection (Common/Differential) -	
Power Consumption	2,000 W	Sustainability rating	-
Connection	Screw connector	Protection class IEC	Safety class I
Cable	-		
		Application Conditions	
Temperature		Maximum dim level	Not applicable
Ambient temperature range	-30 to +35 ℃		
		Product Data	
Controls and Dimming		Order product name	MVF404 MHN-SEH2000W/956 380-415V B3
Dimmable	No		SI A
Constant light output	No	Full product name	MVF404 MHN-SEH2000W/956 380-415V B3
			SI A
Mechanical and Housing		Full product code	872790050216900
Housing Material	Aluminum	Order code	50216900
Reflector material	Aluminum	Material Nr. (12NC)	910502219718
Optic material	Aluminum	Numerator - Quantity Per Pack	1
Optical cover material	-	EAN/UPC - Product/Case	8727900502169
Fixation material	Steel	Numerator - Packs per outer box	1
Housing Color	Aluminum	EAN/UPC - Case	8727900502169
Mounting device	Mounting bracket adjustable		
Optical cover shape	_		

Dimensional drawing



ArenaVision MVF404



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, June 30 - data subject to change