



Tempo 2 RVP251

RVP251 CDM-TD150W/830 IC A

MASTERColour CDM-TD, 150 W, Asymmetrical

Tempo is a complete floodlighting range offering a wide choice of lamp types and symmetrical and asymmetrical reflectors. It is designed for general-purpose floodlighting, and is particularly suited to small- to medium-scale area or surface lighting. The Tempo series' compact housing guarantees optimum visual integration. Anodized-aluminum reflectors ensure a highly efficient beam distribution, while the nylon bolt caps feature a goniometric aiming device for easy adjustment and alignment. A universal mounting bracket allows ceiling, wall or surface mounting with a wide range of adjustment for both down- and uplighting. Tempo's all-weather construction is designed to make cleaning and servicing easy and fast. Access to the lamp and gear is simple, via the hinged front glass with its quick-release stainless-steel clips. All Tempo luminaires are RoHS-compliant.

Product data

General Information		Optical cover type	
Lamp family code	CDM-TD [MASTERColour CDM-TD]	Optic type outdoor	Asymmetrical
Gear	CONV [Conventional]		
CE mark	Yes	Operating and Electrical	
ENEC mark	-	Input Voltage	230 V
Warranty period	1 years	Line Frequency	50 Hz
EU RoHS compliant	Yes	Initial CLO power consumption	{NO} - W
		End CLO power consumption	{NO} - W
		Power Consumption	150 W
Light Technical		Power Factor (Fraction)	0.85
Upward light output ratio	0	Connection	Screw connection block 3-pole
Correlated Color Temperature (Nom)	3000 K	Cable	-
Color rendering index (CRI)	80		
Number of light sources	1		
Light source color	830 warm white		

Tempo 2 RVP251

Temperature

Ambient temperature range	-25 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Aluminum
Optic material	Aluminum
Optical cover material	Glass
Fixation material	Steel
Housing Color	Grey
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	346 mm
Overall width	363 mm
Overall height	118 mm
Effective projected area	0.123 m²

Dimensions (Height x Width x Depth)	118 x 363 x 346 mm
-------------------------------------	--------------------

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I

Product Data

Order product name	RVP251 CDM-TD150W/830 IC A
Full product name	RVP251 CDM-TD150W/830 IC A
Full product code	871155914956100
Order code	910502547018
Material Nr. (12NC)	910502547018
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711559149561
Numerator - Packs per outer box	1
EAN/UPC - Case	8711559149561

Dimensional drawing

