



Tempo 1 RVP151

RVP151 SON-TPP70W K IC A

SON-T PIA Plus, 70 W, Asymmetrical

Tempo is a complete floodlighting range offering a wide choice of lamp types and symmetrical and asymmetrical reflectors. It is designed for general-purpose floodlighting, and is particularly suited to small- to medium-scale area or surface lighting. The Tempo series' compact housing guarantees optimum visual integration. Anodized-aluminum reflectors ensure a highly efficient beam distribution, while the nylon bolt caps feature a goniometric aiming device for easy adjustment and alignment. A universal mounting bracket allows ceiling, wall or surface mounting with a wide range of adjustment for both down- and uplighting. Tempo's all-weather construction is designed to make cleaning and servicing easy and fast. Access to the lamp and gear is simple, via the hinged front glass with its quick-release stainless-steel clips. All Tempo luminaires are RoHS-compliant.

Product data

General Information		Optical cover type	
Lamp family code	SON-TPP [SON-T PIA Plus]	Flat glass	
Gear	CONV [Conventional]	Optic type outdoor	
CE mark	Yes	Asymmetrical	
ENEC mark	-		
Warranty period	1 years	Operating and Electrical	
EU RoHS compliant	Yes	Input Voltage	
		230 V	
		Line Frequency	
		50 Hz	
		Initial CLO power consumption	
		{NO} - W	
		End CLO power consumption	
		{NO} - W	
		Power Consumption	
		70 W	
		Power Factor (Fraction)	
		0.85	
		Connection	
		Screw connection block 3-pole	
		Cable	
		-	
Light Technical			
Upward light output ratio	0		
Correlated Color Temperature (Nom)	2000 K		
Color rendering index (CRI)	25		
Number of light sources	1		
Light source color	220 gold		

Tempo 1 RVP151

Temperature	
Ambient temperature range	-25 to +35 °C
Controls and Dimming	
Dimmable	No
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Reflector material	Aluminum
Optic material	Aluminum
Optical cover material	Glass
Fixation material	Steel
Housing Color	Grey
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	303 mm
Overall width	306 mm
Overall height	109 mm
Effective projected area	0.08 m²

Dimensions (Height x Width x Depth)	109 x 306 x 303 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I
Product Data	
Order product name	RVP151 SON-TPP70W K IC A
Full product name	RVP151 SON-TPP70W K IC A
Full product code	871155980669300
Order code	910502556218
Material Nr. (12NC)	910502556218
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711559806693
Numerator - Packs per outer box	1
EAN/UPC - Case	8711559806693

Dimensional drawing

