



ParkView LED

BPS965 GRN49/840 NOIR CLO-DDF6 114P C4K

Parkview LED, LED GreenLine 4500 lm, Constant light output and DynaDimmer fixed presets version 6, Post-top for diameter 114 mm

For urban settings, customers want a luminaire that combines unobtrusive elegance with operational efficiency. ParkView LED's unique construction of clear polycarbonate and white lamellas gives the luminaire a sense of lightness and minimalism. Its cone-shaped bowl marked in quarters, cone-shaped louver and base ensure a smooth transition to the pole. ParkView LED provides a symmetrical light distribution, and the vertical lamellas which direct the light towards the ground also cut spill light and minimize glare as they shield the light source. Design: Tegnestuen Bjarne Frost, Denmark

Product data

General Information	
Lamp family code	GRN45 [LED GreenLine 4500 lm]
Light source replaceable	Yes
Driver included	Yes
Product family code	BPS965 [Parkview LED]
Lighting Technology	LED
CE mark	Yes
Embedded control	Constant light output and DynaDimmer fixed
	presets version 6
Light Technical	
Light recinicat	
Luminous Flux	4,900 lm
	,,,,,,,
Luminous Flux	,,,,,,,

Color rendering index (CRI)	83
Number of light sources	1
Light source color	840 neutral white
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Power Consumption	47 W
Cable	Cable 4.0 m without plug
Temperature	
Ambient temperature range	-30 to +25 °C

Datasheet, 2023, September 4 data subject to change

ParkView LED

Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Power supply unit regulating
Control interface	-
Constant light output	Yes
Mechanical and Housing	
Housing Material	Aluminum
Mounting device	Post-top for diameter 114 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class II

re +/-2
BPS965 GRN49/840 NOIR CLO-DDF6 114P C4K
BPS965 GRN49/840 NOIR CLO-DDF6 114P C4K
871829156020300
910502610438
910502610438
1
8718291560203
1
8718291560203

Dimensional drawing





