



UnicOne Compact LED, pendant

BPK561 DLM3000-/840 PSU WB GR

Unicone, Fortimo LED module DLM 3000, 840 neutral white, Power supply unit (On/Off), Wide beam, Grey

Across the retail sector, store owners want perfect-quality illumination in order to show their merchandize in the very best light. At the same time, they are under pressure to reduce energy and maintenance costs. UnicOne Pendant LED is a decorative suspended luminaire designed for use above, for example, cashier zones and display islands in supermarkets, furniture stores and fashion outlets. Incorporating the latest-generation Fortimo DLM module, it delivers significant energy savings compared to CHID solutions, as well as eliminating multiple relamping cycles. A dedicated version for enhancement of fresh food produce, with reduced UV and heat emission, is also available. UnicOne Pendant LED features a subtle conical lamp housing – a pure look & feel that will enhance any store interior.

Product data

General Information			
Lamp family code	DLM3000 [Fortimo LED module DLM 3000]		useful life (B50) value also represents the B10 value.
Light source replaceable	No	Product family code	BPK561 [Unicone]
Gear	-	CE mark	Yes
Driver included	Yes	Flammability mark	For mounting on normally flammable surfaces
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median	ENEC mark	ENEC mark
		Glow-wire test	Temperature 850 °C, duration 5 s
Light Technical			
Luminous Flux	3,000 lm		
Correlated Color Temperature (Nom)	4000 K		

UnicOne Compact LED, pendant

Luminous Efficacy (rated) (Nom)	65 lm/W
Color rendering index (CRI)	≥80
Number of light sources	1
Light source color	840 neutral white
Optic type	Wide beam

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Power Consumption	46 W

Temperature

Ambient temperature range	+10 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)

Mechanical and Housing

Housing Material	Aluminum
Housing Color	Grey

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I

Application Conditions

Performance ambient temperature T _a	25 °C
Suitable for random switching	Not applicable

Product Data

Order product name	BPK561 DLM3000-/840 PSU WB GR
Full product name	BPK561 DLM3000-/840 PSU WB GR
Full product code	871829101537600
Order code	910503508815
Material Nr. (12NC)	910503508815
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291015376
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291015376

Dimensional drawing

