



eW Fuse Powercore Precision Dimming

LS515X LED5/4000 100-277V MB WH

eW Fuse Powercore, 4000 K, 30° x 60° beam angle, 12.5 W/ft, 305 mm (1 ft)

With narrow and medium beams of intense white light, eW Fuse Powercore Precision Dimming is an excellent choice for a full range of surface grazing and wall-washing applications. Its ultra-compact form factor permits installation in tight spaces too small to accommodate conventional grazing fixtures with similar light output. eW Fuse Powercore Precision Dimming meets or exceeds the performance of comparable linear fluorescent grazing fixtures while lowering installation, energy, and maintenance costs. It offers environmentally-conscious buyers a green, energy-efficient grazing fixture with industry-leading quality and quantity of light.Integrated Powercore technology ensures rapid, efficient and accurate control of power output to the fixture directly from line voltage, eliminating the need for external power supplies.

Product data

General Information	
Lamp family code	LED5 [LED Module 500 lm]
Lamp colour code	840 neutral white
Light source replaceable	No
Driver included	Yes
Optic type	MB [Medium beam]
Luminaire light beam spread	30° x 60°
Protection class IEC	Safety class I (I)
Glow-wire test	850/5 [Temperature 850 °C, duration 5 s]
Type description	No

CE mark	CE mark
0 "	
Operating and Electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes

Datasheet, 2022, February 21 data subject to change

eW Fuse Powercore Precision Dimming

Mechanical and Housing		
Housing material	Aluminium	
Length	305 mm	
Colour	White	
Approval and Application		
Ingress protection code	IP20 [Finger-protected]	
Mech. impact protection code	IK02 [0.2 J standard]	
Initial Performance (IEC Compliant)		
Initial luminous flux (system flux)	500 lm	
Lamp colour temperature	4000 K	
Initial input power	13.5 W	
Application Conditions		
Ambient temperature range	-40 to +50 ℃	
Maximum dimming level	10% (depends on dimmer, ELV)	


Suitable for random switching	Yes
Product Data	
Full product code	871829137624899
Order product name	LS515X LED5/4000 100-277V MB WH
EAN/UPC – product	8718291376248
Order code	523-000065-15
SAP numerator – quantity per pack 1	
Numerator – packs per outer box	20
SAP material	910503701724
SAP net weight (piece)	0.435 kg
Commercial Code	523-000065-15
Commercial Code	eW Fuse Powercore, 4000 K, 30° x 60° beam angle,
	12.5 W/ft, 305 mm (1 ft)







Dimensional drawing



LS515X LED5/4000 100-277V MB WH



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.