



iW Burst Compact Powercore

iW Burst Compact Powercore, 10° x 41° Spread Lens, Black Housing, UL/cUL/CE, Architectural

iW Burst Compact Powercore, 10° x 41° Spread Lens, Black Housing, UL/cUL/CE, Architectural

iW Burst Compact Powercore is a high-output, exterior-rated LED spotlight designed for accent and site lighting. It combines channels of warm and cool LEDs to offer variable color temperatures ranging from warm to cool. Standard and compact format Architectural and Landscape versions support a range of uplighting, floodlighting, and decorative lighting applications. Integrated Powercore technology ensures rapid, efficient and accurate control of power output to the fixture directly from line voltage, eliminating the need for external power supplies. Use of standard wiring dramatically simplifies installation and helps lower total system cost.

Product data

General Information	
Number of light sources	12 [12 pcs]
Lamp family code	LED-HB [LED High Brightness]
Light source colour	Cool white and warm white
Light source replaceable	No
Driver included	No
Optical cover/lens type	GT [Tempered glass]
Luminaire light beam spread	8°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark

Lifetime to 50% luminous flux	50000 h	
Lifetime to 70% luminous flux	50000 h	
Operating and Electrical		
Input Voltage	100 to 240 V	
Input frequency	50 to 60 Hz	
Controls and Dimming		
Dimmable	Yes	

Datasheet, 2021, August 17 data subject to change


iW Burst Compact Powercore

Mechanical and Housing	
Housing configuration	BV [Basic version]
Colour	Black
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-
	proof]
Vibration standard	Complies with ANSI C136.31, 3G
Vibration rating	Complies with ANSI C136.31, 3G
Initial Performance (IEC Complian	it)
Initial input power	17.5 W
Over Time Performance (IEC Com	pliant)
Lumen Maintenance 50% at 25 °C	50000
Reported	
Lumen Maintenance 50% at 50 °C	50000
Reported	
Lumen Maintenance 70% at 25 °C Report	rted 50000

Lumen Maintenance 70% at 50 °C	35000
Reported	
Product Data	
Full product code	871794379292499
Order product name	BCP464 12xLED-HB-2700-6500 BK ULCE
EAN/UPC – product	8717943792924
Order code	523-000067-04
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	910503702209
SAP net weight (piece)	3.500 kg
Commercial Code	523-000067-04
Catalogue number description	iW Burst Compact Powercore, 10° x 41°
	Spread Lens, Black Housing, UL/cUL/CE,
	Architectural



Dimensional drawing



iW Burst Compact Powercore



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.