



# Vaya Flood HP

## BCP417 48xLED-HB/RGB 100-277V 40 CE CQC

48 pcs - LED High Brightness - Medium beam angle 40°

Vaya Flood HP is a reliable and cost-effective white/color-changing floodlight, designed for large-scale exterior installations. The light levels achieved by this compact fixture make it ideal for extensive wall-washing and floodlighting applications – in both static or dynamic colors. Integrated power and DMX512 control make this product easy to use with Philips or third-party DMX controllers.

#### **Product data**

General Information	
Number of light sources	48 [ 48 pcs]
Lamp family code	LED-HB [ LED High Brightness]
Light source color	Red, green and blue (RGB)
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	FG [ Flat glass]
Luminaire light beam spread	40°
Protection class IEC	Safety class I (I)
Type description	No
CE mark	CE mark
ENEC mark	ENEC mark
UL mark	-
CQC mark	CQC-mark
Optic type outdoor	Medium beam angle 40°
PSE mark	PSE mark
RoHS mark	-
WEEE mark	-
Angle	40°

Light Technical	
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Operating and Electrical	
Input Voltage	100 to 277 V
Input Frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum die-cast
Optic material	Glass
Optical cover/lens material	Tempered glass
Optical cover/lens shape	Flat
Approval and Application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
9	


Datasheet, 2018, December 3 data subject to change

## Vaya Flood HP

Mech. impact protection code	IK06 [ 1 J]	
Initial Performance (IEC Compliant)		
Initial luminous flux (system flux)	3401 lm	
Initial LED luminaire efficacy	31.7 lm/W	
Init. Color Rendering Index	80	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 50% at 25°C Calculated	100000	
Lumen Maintenance 50% at 25°C Reported	60000	
Lumen Maintenance 70% at 25°C Calculated	100000	
Lumen Maintenance 70% at 25°C Reported	60000	
Application Conditions		
Ambient temperature range	-40 to +104 °F	

871829163494299
BCP417 48xLED-HB/RGB 100-277V 40 CE CQC
8718291634942
910503702886
1
2
910503702886
7.500 kg

### Dimensional drawing



Vava

