



eColor Graze QLX Powercore

eColor Graze QLX Powercore, Green, 15° x 30° Beam Angle, 914 mm (3 ft)

Green - 15° x 30° - 914 mm - Aluminum

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze QLX Powercore is capable of illuminating over 10 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	Green
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PC-UV [Polycarbonate bowl/cover UV-resistant]
Luminaire light beam spread	15° x 30°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	100000 h
Operating and Electrical	
Input Voltage	100 to 277 V

Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminum extruded
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	914 mm
Colour	Aluminum
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]

Datasheet, 2020, December 15 data subject to change


eColor Graze QLX Powercore

Vibration standard Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations. Vibration rating Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations. Initial Performance (IEC Compliant) Initial input power 42 W Application Conditions Ambient temperature range -40 to +50 °C			
contact your Color Kinetics Lighting Sales rep for custom configurations. Vibration rating Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations. Initial Performance (IEC Compliant) Initial input power 42 W Application Conditions	Vibration standard	Not compliant to ANSI C136.31, 3G. Special orders	
custom configurations. Vibration rating Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations. Initial Performance (IEC Compliant) Initial input power 42 W Application Conditions		are available to conform to the standard. Please	
Vibration rating Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations. Initial Performance (IEC Compliant) Initial input power 42 W Application Conditions		contact your Color Kinetics Lighting Sales rep for	
are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations. Initial Performance (IEC Compliant) Initial input power 42 W Application Conditions		custom configurations.	
contact your Color Kinetics Lighting Sales rep for custom configurations. Initial Performance (IEC Compliant) Initial input power 42 W Application Conditions	Vibration rating	Not compliant to ANSI C136.31, 3G. Special orders	
custom configurations. Initial Performance (IEC Compliant) Initial input power 42 W Application Conditions		are available to conform to the standard. Please	
Initial Performance (IEC Compliant) Initial input power 42 W Application Conditions		contact your Color Kinetics Lighting Sales rep for	
Initial input power 42 W Application Conditions		custom configurations.	
Initial input power 42 W Application Conditions			
Application Conditions	Initial Performance (IEC Compliant)		
	Initial input power	42 W	
Ambient temperature range -40 to +50 °C	Application Conditions		
	Ambient temperature range	-40 to +50 °C	

Product Data	
Full product code	871829160626000
Order product name	BCS447 15x30 GN L914
EAN/UPC – product	8718291606260
Order code	223-000081-49
SAP numerator – quantity per pack 1	
Numerator – packs per outer box	1
SAP material	910503703519
Net Weight (Piece)	3.800 kg
Commercial Code	223-000081-49
Commercial Code	eColor Graze QLX Powercore, Green, 15° x 30° Beam
	Angle, 914 mm (3 ft)



Dimensional drawing





© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.