



iW Graze QLX Powercore

iW Graze QLX Powercore, 60° x 30° Beam Angle, 610 mm (2 ft)

iW Graze QLX Powercore, 60° x 30° Beam Angle, 610 mm (2 ft)

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze QLX Powercore is capable of illuminating over 10 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

General Information		Controls and Dimming	
Lamp family code	LED-HB [LED High Brightness]	Dimmable	Yes
Light source replaceable	No		
Driver included	Yes	Mechanical and Housing	
Luminaire light beam spread	60° x 30°	Length	609 mm
Protection class IEC	Safety class I	Approval and Application	
CE mark	CE mark	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
UL mark	UL mark	Mech. impact protection code	IK10 [20 J vandal-resistant]
Lifetime to 70% luminous flux	100000 h	Vibration standard	Complies with ANSI C136.31, 3G
Operating and Electrical		Vibration rating	Complies with ANSI C136.31, 3G
Input Voltage	100 to 277 V	Initial Performance (IEC Compliant)	
Input frequency	50 to 60 Hz	Initial input power	30 W

iW Graze QLX Powercore

Application Conditions	
Ambient temperature range	-20 to +50 °C
Product Data	
Full product code	871829160988999
Order product name	BCS437 60x30/2700-6500 L609
EAN/UPC – product	8718291609889
Order code	523-000079-29
SAP numerator – quantity per pack	1

Numerator – packs per outer box	4
SAP material	910503703673
SAP net weight (piece)	2.700 kg
Commercial Code	523-000079-29
Catalogue number description	iW Graze QLX Powercore, 60° x 30° Beam Angle, 610 mm (2 ft)



Dimensional drawing

