



eW Graze MX Powercore

BCS419 10x60/5500 L914

eW Graze MX Powercore, 5500 K, 10° x 60° Beam Angle, 914 mm (3 ft)

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	Neutral white
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	10° x 60°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	60000 h
Operating and Electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Extruded aluminium
Optical cover/lens material	Polycarbonate
Length	914 mm
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Not compliant to ANSI C136.31, 3G. Special
	orders are available to conform to the standard.
	Please contact your Color Kinetics Lighting
	Sales rep for custom configurations.

Datasheet, 2022, February 21 data subject to change

eW Graze MX Powercore


Vibration rating	Not compliant to ANSI C136.31, 3G. Special
	orders are available to conform to the standard.
	Please contact your Color Kinetics Lighting
	Sales rep for custom configurations.
Initial Performance (IEC Complia	unt)
Init. Corr. Colour Temperature	5500 K
Initial input power	42 W
Over Time Performance (IEC Cor	mpliant)
Lumen Maintenance 50% at 25 °C	60000
Reported	
Lumen Maintenance 50% at 50 °C	60000
Reported	
Lumen Maintenance 70% at 25 °C	60000
Reported	
Lumen Maintenance 70% at 50 °C	60000
Reported	

Application Conditions	
Ambient temperature range	-20 to +50 °C
Product Data	
Full product code	871829161048900
Order product name	BCS419 10x60/5500 L914
EAN/UPC – product	8718291610489
Order code	523-000080-35
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	910503703723
SAP net weight (piece)	3.800 kg
Commercial Code	523-000080-35
Catalogue number description	eW Graze MX Powercore, 5500 K, 10° x 60°
	Beam Angle, 914 mm (3 ft)





Dimensional drawing



BCS419 10x60/5500 L914



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.