



eW Graze MX Powercore

BCS419 10x60/5500 L1219

eW Graze MX Powercore, 5500 K, 10° x 60° Beam Angle, 1219 mm (4 ft)

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

General Information		Controls and Dimming	
Lamp family code	LED-HB [LED High Brightness]	Dimmable	Yes
Light source colour	Neutral white		
Light source replaceable	No	Mechanical and Housing	
Driver included	Yes	Housing material	Extruded aluminium
Luminaire light beam spread	10° x 60°	Optical cover/lens material	Polycarbonate
Protection class IEC	Safety class I	Length	1219 mm
CE mark	CE mark	Approval and Application	
UL mark	UL and cUL mark	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Lifetime to 70% luminous flux	60000 h	Mech. impact protection code	IK10 [20 J vandal-resistant]
Operating and Electrical		Vibration standard	Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations.
Input Voltage	100 to 277 V		
Input frequency	50 to 60 Hz		

eW Graze MX Powercore

Vibration rating	Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations.
------------------	--

Initial Performance (IEC Compliant)

Init. Corr. Colour Temperature	5500 K
Initial input power	60 W

Over Time Performance (IEC Compliant)

Lumen Maintenance 50% at 25 °C	60000
Reported	
Lumen Maintenance 50% at 50 °C	60000
Reported	
Lumen Maintenance 70% at 25 °C	60000
Reported	
Lumen Maintenance 70% at 50 °C	60000
Reported	

Application Conditions	
Ambient temperature range	-20 to +50 °C
Product Data	
Full product code	871829161063200
Order product name	BCS419 10x60/5500 L1219
EAN/UPC – product	8718291610632
Order code	523-000080-50
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	910503703738
SAP net weight (piece)	4.700 kg
Commercial Code	523-000080-50
Catalogue number description	eW Graze MX Powercore, 5500 K, 10° x 60° Beam Angle, 1219 mm (4 ft)



Dimensional drawing

