



eW Graze EC Powercore

BCS428 4000 L305

eW Graze EC Powercore, 4000 K, 90° x 90° Beam Angle, 305 mm (1 ft)

Some exterior architectural details require a soft-edged volume fill of light. Graze EC Powercore combines this output with the proven, durable design of the Graze Powercore product family and low power consumption.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	Neutral white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PCF [Polycarbonate bowl/cover frosted]
Luminaire light beam spread	90° x 90°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	36000 h
Operating and Electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminum extruded
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	305 mm
Colour	Aluminum
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Complies with ANSI C136.31, 3G
Vibration rating	Complies with ANSI C136.31, 3G

eW Graze EC Powercore

Initial Performance (IEC Complian	t)	
Initial luminous flux (system flux)	245 lm	
Init. Corr. Colour Temperature	4000 K	
Init. Colour rendering index	87	
Initial input power	15 W	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 50% at 25 °C Reported 36000		
Lumen Maintenance 50% at 50 °C Reported 36000		
Lumen Maintenance 70% at 25 °C Reported 36000		
Lumen Maintenance 70% at 50 °C Repo	rted 36000	
Application Conditions		

-40 to +50 °C


371829161194399
3CS428 4000 L305
3718291611943
23-00082-01
1
910503703808
.200 kg
23-00082-01
eW Graze EC Powercore, 4000 K, 90° x 90°
3eam Angle, 305 mm (1 ft)

Application Conditions

Ambient temperature range



Dimensional drawing



BCS428 4000 L305



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2022, February 21 - data subject to change