



# eW Graze EC Powercore

## BCS428 2700 L914

eW Graze EC Powercore, 2700 K,  $90^{\circ}$  x  $90^{\circ}$  Beam angle, 914 mm (3 ft)

Some exterior architectural details require a soft-edged volume fill of light. Graze EC Powercore combines this output with the proven, durable design of the Graze Powercore product family and low power consumption.

### Product data

General Information	
Lamp family code	LED-HB [ LED High Brightness]
Light source colour	Warm white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PCF [ Polycarbonate bowl/cover frosted]
Luminaire light beam spread	90° x 90°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	36000 h
Operating and Electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Extruded aluminium
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	914 mm
Colour	Aluminium
Approval and Application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [ 20 J vandal-resistant]
Vibration standard	Not compliant to ANSI C136.31, 3G. Special
	orders are available to conform to the
	standard. Please contact your Color Kinetics
	Lighting Sales rep for custom configurations.

Datasheet, 2022, February 21 data subject to change


# **eW Graze EC Powercore**

Vibration rating	Not compliant to ANSI C136.31, 3G. Special
	orders are available to conform to the
	standard. Please contact your Color Kinetics
	Lighting Sales rep for custom configurations.
Initial Performance (IEC Complia	ant)
Init. Corr. Colour Temperature	2700 K
Init. Colour rendering index	80
Initial input power	42 W
Over Time Performance (IEC Co	mpliant)
Lumen Maintenance 50% at 25 °C	36000
Reported	
Lumen Maintenance 50% at 50 °C	36000
Reported	
Lumen Maintenance 70% at 25 °C	36000
Reported	
Lumen Maintenance 70% at 50 °C	36000
Reported	

Application Conditions	
Ambient temperature range	-40 to +50 ℃
Product Data	
Full product code	871829161199800
Order product name	BCS428 2700 L914
EAN/UPC – product	8718291611998
Order code	523-000082-06
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	910503703813
SAP net weight (piece)	3.800 kg
Commercial Code	523-000082-06
Catalogue number description	eW Graze EC Powercore, 2700 K, 90° x 90°
	Beam angle, 914 mm (3 ft)



# Dimensional drawing



BCS428 2700 L914



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.