



ColorGraze MX4 Powercore

BCS559 15x30 RGBW L1219

RGBW - 15° x 30° - 1219 mm

High-output luminaire for high-intensity multi-story façade and surface illumination at minimal setback; RGBW and RGBA options provide an expanded color palette and white light capability in one fixture.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Lamp colour code	RGBW
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PC [Polycarbonate bowl/cover]
Luminaire light beam spread	15° x 30°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Operating and Electrical	
Input voltage	100 to 277 V
Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Housing material	Aluminum extruded
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	1219 mm
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Not compliant to ANSI C136.31, 3G. Special
	orders are available to conform to the
	standard. Please contact your Color Kinetics
	Lighting Sales rep for custom configurations.
	Not compliant to ANSI C136.31, 3G. Special
	orders are available to conform to the
	standard. Please contact your Color Kinetics
	Lighting Sales rep for custom configurations.


Datasheet, 2019, September 16 data subject to change

ColorGraze MX4 Powercore

Initial Performance (IEC Compliant)		
Initial luminous flux	2488 lm	
Initial LED luminaire efficacy	34.4 lm/W	
Initial input power	74 W	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 50% at 25°C	75000	
Reported		
Lumen Maintenance 50% at 50°C	70000	
Reported		
Lumen Maintenance 70% at 25°C	100000	
Calculated		
Lumen Maintenance 70% at 25°C	70000	
Reported		
Lumen Maintenance 70% at 50°C	100000	
Calculated		
Lumen Maintenance 70% at 50°C	65000	
Reported		

Application Conditions	
Ambient temperature range	-40 to +50 ℃
Product Data	
Full product code	871829161964200
Order product name	BCS559 15x30 RGBW L1219
EAN/UPC – product	8718291619642
Order code	910503704698
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910503704698
Net weight (piece)	4.700 kg

Dimensional drawing





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.