



CoreLine panel

RC127V LED34S/830 PSU W60L60 OC

CoreLine panel, 41 W, 600x600 mm, 3400 lm, 3000 K, UGR19

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Panel range of LED products can be used to replace functional luminaires in general lighting applications. Both Non-Office Compliant (NOC) version and Office Compliant version (OC) are now available. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data

General Information		EU RoHS compliant	
Lamp family code	LED34S [LED module, system flux 3400 lm]	Yes	
Light source replaceable	No		
Number of gear units	1 unit		
Driver included	Yes		
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.		
Lighting Technology		Light Technical	
Value ladder	Performance	Luminous Flux	3,400 lm
CE mark	Yes	Correlated Color Temperature (Nom)	3000 K
Warranty period	3 years + 2 years upon registration	Luminous Efficacy (rated) (Nom)	83 lm/W
Flammability mark	For mounting on normally flammable surfaces	Color rendering index (CRI)	≥80
ENEC mark	ENEC mark	Light source color	830 warm white
Glow-wire test	Temperature 650 °C, duration 30 s	Optic type	-
		Luminaire light beam spread	100°
		Unified glare rating CEN	19
		Operating and Electrical	
		Input Voltage	220 to 240 V
		Line Frequency	50 to 60 Hz
		Inrush current	17 A
		Inrush time	0.25 ms
		Power Consumption	41 W
		Power Factor (Fraction)	0.9

CoreLine panel

Connection	Push-in connector and pull relief
Cable	-
Number of products on MCB of 16 A type B	28

Temperature

Ambient temperature range	+10 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	-
Optical cover material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover finish	Opal
Overall length	597 mm
Overall width	597 mm
Overall height	42 mm
Dimensions (Height x Width x Depth)	42 x 597 x 597 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.44, 0.41) SDCM <5
Power consumption tolerance	+/-10%


Application Conditions

Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes

Product Data

Order product name	RC127V LED34S/830 PSU W60L60 OC
Full product name	RC127V LED34S/830 PSU W60L60 OC
Full product code	871869607089500
Order code	07089500
Material Nr. (12NC)	910503910320
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696070895
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696070895

Dimensional drawing



CoreLine panel

