



SmartBalance Wall-mounted

WL484W LED40S/840 PSD D/I SW WH

SmartBalance wall-mounted, LED module, system flux 4000 lm, 840 neutral white, Power supply unit with DALI interface, White

Striking the right balance between the different lighting needs in a patient room is a challenge for many hospitals. That's why our bed-head luminaires offer some of the key functionalities required by both patients and staff. The SmartBalance, wall-mounted luminaire combines high-quality lighting performance with a stylish, timeless design. General ambience light is provided indirectly via the upper part of the luminaire. The lower part delivers direct, diffuse light, allowing patients to read and clinical staff to carry out examinations at the bed.

Product data

General Information			
Lamp family code	LED40S [LED module, system flux 4000 lm]	Product family code	WL484W [SmartBalance wall-mounted]
Cap base	- [-]	Lighting Technology	LED
Light source replaceable	No	Embedded control	-
Number of gear units	2 units	CE mark	Yes
Gear	-	Warranty period	5 years
Driver included	Yes	Flammability mark	For mounting on normally flammable surfaces
Remarks	*- According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median useful life (B50) value also represents the B10 value.	ENEC mark	ENEC plus mark
		Glow-wire test	Temperature 650 °C, duration 5 s
		EU RoHS compliant	Yes
		Light Technical	
		Luminous Flux	4,000 lm
		Correlated Colour Temperature	4000 K
		Luminous efficacy (rated) (nom.)	122 lm/W

SmartBalance Wall-mounted

Colour rendering index (CRI)	≥80
Beam angle of light source	- degree(s)
Light source colour	840 neutral white
Optic type	-
Optical cover type	Polycarbonate bowl/cover
Luminaire light beam spread	156°

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	48 A
Inrush time	0.18 ms
Power Consumption	32.7 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 5-pole
Cable	-
Number of products on MCB of 16 A type B	20

Temperature

Ambient temperature range	0 to +35 °C
---------------------------	-------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	DALI
Constant light output	No

Mechanical and Housing

Housing material	Aluminium
Reflector material	Aluminium
Optic material	-
Optical cover/lens material	Polycarbonate
Fixation material	Stainless steel

Housing Colour	White
Optical cover/lens finish	Textured
Overall length	900 mm
Overall width	152 mm
Overall height	52 mm
Dimensions (height x width x depth)	52 x 152 x 900 mm

Approval and Application

Ingress protection code	IP40 [Wire-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM <3
Power consumption tolerance	+/-10%


Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	1%
Suitable for random switching	No

Product Data

Order product name	WL484W LED40S/840 PSD D/I SW WH
Full product name	WL484W LED40S/840 PSD D/I SW WH
Full EOC	871869686902400
Order code	86902400
Material no. (12 NC)	910504096303
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718696869024
Numerator – packs per outer box	1
EAN/UPC – Case	8718696869024

Dimensional drawing



SmartBalance Wall-mounted

