



# TrueLine, surface mounted

## SM530C LED40S/840 PSD PI5 L1130 ALU

TrueLine OC, LED module, system flux 4000 lm, 840 neutral white, Power supply unit with DALI interface, Push-in connector 5-pole, Aluminium

Architects need a lighting solution that matches the interior architecture of the property they are working on. They want a light line with an elegant design and very high light levels. Specifiers need luminaires that enable them to save energy while at the same time providing the right level of light, in compliance with office lighting norms. And office workers want visually comfortable lighting conditions that help them perform better. TrueLine Recessed is able to meet all of these different requirements. TrueLine is also available in recessed and suspended versions.

### Warnings and Safety

- The product is IP40 and as such is not protected against water ingress, so we strongly recommend that the environment in which the luminaire is to be installed is suitably checked
- If the above advice is not taken and the luminaires are subject to water ingress, Philips/Signify cannot guarantee safe use and the product warranty will become void

### Product data

General information	
Lamp family code	LED40S [LED module, system flux 4000 lm]
Cap base	- [-]
Light source replaceable	No
Number of gear units	Unit
Gear	-
Driver included	Yes

Remarks
*- According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median

## TrueLine, surface mounted

	useful life (B50) value also represents the B10 value.
<b>Product family code</b>	SM530C [TrueLine OC]
<b>Lighting Technology</b>	LED
<b>Value ladder</b>	Specification
<b>CE mark</b>	Yes
<b>Warranty period</b>	5 years
<b>Flammability mark</b>	For mounting on normally flammable surfaces
<b>ENEC mark</b>	ENEC plus mark
<b>Glow-wire test</b>	Temperature 650 °C, duration 5 s
<b>EU RoHS compliant</b>	Yes

### Light Technical

<b>Luminous Flux</b>	4,000 lm
<b>Correlated Colour Temperature</b>	4000 K
<b>Luminous efficacy (rated) (nom.)</b>	138 lm/W
<b>Colour rendering index (CRI)</b>	≥80
<b>Beam angle of light source</b>	- degree(s)
<b>Light source colour</b>	840 neutral white
<b>Optic type</b>	-
<b>Optical cover type</b>	Polymethyl methacrylate bowl/cover
<b>Luminaire light beam spread</b>	100°
<b>Unified Glare Rating (CEN)</b>	19

### Operating and Electrical

<b>Input Voltage</b>	220 to 240 V
<b>Line Frequency</b>	50 to 60 Hz
<b>Inrush current</b>	19 A
<b>Inrush time</b>	0.28 ms
<b>Power Consumption</b>	29 W
<b>Power Factor (Fraction)</b>	0.9
<b>Connection</b>	Push-in connector 5-pole
<b>Cable</b>	-
<b>Number of products on MCB of 16 A type B</b>	24

### Temperature

<b>Ambient temperature range</b>	+10 to +40 °C
----------------------------------	---------------

### Controls and Dimming

<b>Dimmable</b>	Yes
<b>Driver/power unit/transformer</b>	Power supply unit with DALI interface
<b>Control interface</b>	DALI
<b>Constant light output</b>	No

### Mechanical and Housing

<b>Housing material</b>	Aluminium
<b>Reflector material</b>	-
<b>Optic material</b>	-
<b>Optical cover/lens material</b>	Polymethyl methacrylate
<b>Fixation material</b>	Steel
<b>Housing Colour</b>	Aluminium
<b>Optical cover/lens finish</b>	Frosted
<b>Overall length</b>	1,130 mm
<b>Overall width</b>	55 mm
<b>Overall height</b>	93 mm
<b>Dimensions (height x width x depth)</b>	93 x 55 x 1130 mm

### Approval and Application

<b>Ingress protection code</b>	IP40 [Wire-protected]
<b>Mech. impact protection code</b>	IK02 [0.2 J standard]
<b>Protection class IEC</b>	Safety class I

### Initial Performance (IEC Compliant)

<b>Luminous flux tolerance</b>	+/-10%
<b>Initial chromaticity</b>	(0.38, 0.38) SDCM <3
<b>Power consumption tolerance</b>	+/-10%

### Over Time Performance (IEC Compliant)

<b>Control gear failure rate at median useful life 50,000 h</b>	5 %
<b>Lumen maintenance at median useful life* 50,000 h</b>	L85

### Application Conditions

<b>Performance ambient temperature Tq</b>	25 °C
<b>Maximum dim level</b>	1%
<b>Suitable for random switching</b>	No

### Product Data

<b>Order product name</b>	SM530C LED40S/840 PSD PI5 L1130 ALU
<b>Full product name</b>	SM530C LED40S/840 PSD PI5 L1130 ALU
<b>Full EOC</b>	871869687413400
<b>Order code</b>	87413400
<b>Material no. (12 NC)</b>	910504098603
<b>SAP numerator – quantity per pack</b>	1
<b>EAN/UPC – Product/Case</b>	8718696874134
<b>Numerator – packs per outer box</b>	1
<b>EAN/UPC – Case</b>	8718696874134

## TrueLine, surface mounted

### Dimensional drawing

