



# CityCharm Cordoba

## BDS490 CG25-/730 II A GR D11 76

CityCharm Cordoba, 15, LED module, system flux 2500 lm, LED, 730 warm white, Power supply unit regulating, 220 to 240 V, 50 to 60 Hz, Safety class II, Asymmetrical, Polycarbonate bowl/cover, Grey, Luminaire surge protection level up to 6 kV differential mode and 8 kV common mode, Cable 0.2 m without plug, Spigot for diameter 76 mm

CityCharm Cordoba is designed for use in urban areas where comfortable lighting, ambiance and design play an important role. Its unobtrusive appearance makes it a timeless, future-proof luminaire that is ideal for residential areas, parks, footpaths and cycle lanes, where visual comfort and maximum efficiency are key. CityCharm offers a choice of two iconic designs (Cordoba and Cone) and various accessories, enabling you to create a lighting solution that carries your signature, both by day and by night. CityCharm luminaires are also available as a complete set, with a choice of dedicated poles and brackets.

### Product data

General Information			
Lamp family code	CG25 [LED module, system flux 2500 lm]	Product family code	BDS490 [CityCharm Cordoba]
Light source replaceable	Yes	Lighting Technology	LED
Number of gear units	Unit	Value ladder	Performance
Gear	EB [Electronic]	CE mark	Yes
Driver included	Yes	Warranty period	5 years
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components	Flammability mark	-
Light source engine type	LED	ENEC mark	ENEC mark
		Glow-wire test	Temperature 650 °C, duration 5 s
		EU RoHS compliant	Yes

<b>Light Technical</b>	
Upwards light output ratio	0.03
Luminous Flux	2,117 lm
Standard tilt angle post-top	0°
Standard tilt angle side entry	0°
Correlated Colour Temperature	3000 K
Luminous efficacy (rated) (nom.)	96 lm/W
Colour rendering index (CRI)	≥70
Number of light sources	15
Light source colour	730 warm white
Optical cover type	Polycarbonate bowl/cover
Luminaire light beam spread	360°
Optic type outdoor	Asymmetrical
<b>Operating and Electrical</b>	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	27 A
Inrush time	15 ms
Power Consumption	22 W
Power Factor (Fraction)	0.96
Connection	Flying leads/cables
Cable	Cable 0.2 m without plug
Number of products on MCB of 16 A type B	26
<b>Temperature</b>	
Ambient temperature range	-40 to +50 °C
<b>Controls and Dimming</b>	
Dimmable	No
Driver/power unit/transformer	Power supply unit regulating
Control interface	-
Constant light output	No
<b>Mechanical and Housing</b>	
Housing material	Aluminium
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Aluminium
Housing Colour	Grey
Mounting device	Spigot for diameter 76 mm
Optical cover/lens shape	Flat

Optical cover/lens finish	Clear
Overall height	529 mm
Overall diameter	556 mm
Effective projected area	0.1124 m²
<b>Approval and Application</b>	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Surge Protection (Common/Differential)	Luminaire surge protection level up to 6 kV differential mode and 8 kV common mode
Sustainability rating	Lighting for circularity
Protection class IEC	Safety class II
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.430, 0.400) SDCM <3
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2
<b>Over Time Performance (IEC Compliant)</b>	
Driver failure rate at 5,000 hours	0.05 %
Lumen maintenance at median useful life*	L93
100,000 h	
<b>Application Conditions</b>	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
<b>Product Data</b>	
Order product name	BDS490 CG25-/730 II A GR D11 76
Full product name	BDS490 CG25-/730 II A GR D11 76
Full EOC	871869693920800
Order code	93920800
Material no. (12 NC)	910505017425
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718696939208
Numerator – packs per outer box	1
EAN/UPC – Case	8718696939208

### Dimensional drawing

