



# Maxos accessories

## 9MX056 CPI

### Coupling piece internal trunking

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

### Product data

General Information	
Protection class IEC	-
Suspension accessories	CPI [ Coupling piece internal trunking]
Mechanical accessories	No [-]
Packaging configuration	No [-]
Accessory colour	-
Emergency lighting accessories	No [-]
Product Family Code	9MX056 [ ACC MAXOS]
Light Technical	
Optical cover/lens type accessory	No [-]
Operating and Electrical	
Electrical accessories	No [-]

Circuit	No [-]
Mechanical and Housing	
Length	- mm
Dimensions (height x width x depth)	NaN x NaN x NaN mm (NaN x NaN x NaN in)
Approval and Application	
Ingress protection code	- [-]
Product Data	
Full product code	403073210809100
Order product name	9MX056 CPI
EAN/UPC – product	4030732108091
Order code	10809100

## Maxos accessories

Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910681003526

Net weight (piece)	0.220 kg
--------------------	----------

