



Luma Micro

BGP615 LED10-4S/740 PSU I DM10 GR SRG10

LUMA MICRO, LED Module 1000 lm, 740 neutral white, Power supply unit (On/Off), Safety class I, Distribution medium 10, Grey, Spigot for diameter 62 mm

Luma is a high-performance road-lighting luminaire with a clear design identity, offering a perfectly cooled, fit-and-forget solution for all streets and roads. The lumen package, lifetime and energy profile can be tuned to create the desired solution in terms of energy and cost savings. Luma can be programmed to keep the flux of the LEDs at a predefined constant level over the lifetime of the luminaire – by increasing the operating current over time to compensate for the LED lumen depreciation. This eliminates over-lighting at the beginning, enabling additional extra energy savings. Luma uses the high-performance LEDGINE-O engine with latest LED performance and a wide range of optics to latest standards. Moreover, Luma’s truly flat design prevents upward light. To optimize the light distribution for varying road geometries and/or glare restrictions, the tilt angle can easily be adjusted on installation.

Product data

| General Information | | |
|--------------------------|---|--|
| Lamp family code | LED10 [LED Module 1000 lm] | B10. Therefore, the median useful life (B50) value also represents the B10 value. * At extreme ambient temperatures the luminaire might automatically dim down to protect components |
| Light source replaceable | Yes | |
| Number of gear units | 1 unit | |
| Driver included | Yes | |
| Remarks | * -Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example | |
| Light source engine type | | LED |
| Product family code | | BGP615 [LUMA MICRO] |
| Lighting Technology | | LED |
| Flammability mark | | - |
| CE mark | | Yes |

Luma Micro

| | |
|-------------------|-----------|
| ENEC mark | ENEC mark |
| Warranty period | 5 years |
| EU RoHS compliant | No |

Light Technical

| | |
|------------------------------------|------------------------|
| Upward light output ratio | 0 |
| Luminous Flux | 900 lm |
| Standard tilt angle posttop | 0° |
| Standard tilt angle side entry | 0° |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 125 lm/W |
| Color rendering index (CRI) | 70 |
| Light source color | 740 neutral white |
| Optical cover type | Flat glass |
| Luminaire light beam spread | 157° - 33° x 55° |
| Optic type outdoor | Distribution medium 10 |

Operating and Electrical

| | |
|--|-------------------------------|
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 to 60 Hz |
| Inrush current | 15 A |
| Inrush time | 0.295 ms |
| Power Consumption | 7.2 W |
| Power Factor (Fraction) | 0.93 |
| Connection | Screw connection block 3-pole |
| Cable | - |
| Number of products on MCB of 16 A type B | 29 |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Controls and Dimming

| | |
|-------------------------------|----------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Control interface | - |
| Constant light output | No |

Mechanical and Housing

| | |
|------------------------|---------------------------|
| Housing Material | Aluminum |
| Reflector material | Polycarbonate |
| Optic material | Polycarbonate |
| Optical cover material | Glass |
| Fixation material | Aluminum |
| Housing Color | Grey |
| Mounting device | Spigot for diameter 62 mm |

| | |
|-------------------------------------|--------------------|
| Optical cover shape | Flat |
| Optical cover finish | Clear |
| Overall length | 622 mm |
| Overall width | 290 mm |
| Overall height | 130 mm |
| Effective projected area | 0.049 m² |
| Dimensions (Height x Width x Depth) | 130 x 290 x 622 mm |

Approval and Application

| | |
|--|--|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK09 [10 J] |
| Surge Protection (Common/Differential) | Luminaire surge protection level until 10 kV differential mode and 10 kV common mode |
| Protection class IEC | Safety class I |

Initial Performance (IEC Compliant)

| | |
|---------------------------------------|------------------------|
| Luminous flux tolerance | +/-7% |
| Initial chromaticity | (0.381, 0.379) SDCM <5 |
| Power consumption tolerance | +/-10% |
| Init. Color Rendering Index Tolerance | +/-2 |

Over Time Performance (IEC Compliant)

| | |
|--|------|
| Control gear failure rate at median useful life 100000 h | 10 % |
| Lumen maintenance at median useful life* 100000 h | L96 |

Application Conditions

| | |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C |
| Maximum dim level | Not applicable |

Product Data

| | |
|---------------------------------|---|
| Order product name | BGP615 LED10-4S/740 PSU I DM10 GR SRG10 |
| Full product name | BGP615 LED10-4S/740 PSU I DM10 GR SRG10 |
| Full product code | 871869637253100 |
| Order code | 910925452126 |
| Material Nr. (12NC) | 910925452126 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8718696372531 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8718696372531 |

Dimensional drawing

