



UniStreet

BGS203 LED12/740 I DW P1 76A

UniStreet Small, LED Module 1200 lm, 740 neutral white, Safety class I, Distribution wide, Diameter 76 mm adjustable

At relatively low initial cost, the highly efficient LED-based UniStreet luminaire offers significant cost savings compared with conventional street lighting, ensuring full payback within a short period of time. Available in a choice of lumen packages, UniStreet allows point-to-point replacement of outdated conventional light sources and luminaires. The compact, slim luminaire is made of quality recyclable materials. And being a LED solution, it requires little maintenance. Core version design for high-volume projects at relatively low initial budget. Offer limited range of optics. Performer version design for customers who are preparing big renovation projects, TCO oriented

Product data

General Information		
Lamp family code	LED12 [LED Module 1200 lm]	might automatically dim down to protect components
Light source replaceable	Yes	Light source engine type
Number of gear units	1 unit	LED
Driver included	Yes	Product family code
Photocell	NEMA socket for photocell	BGS203 [UniStreet Small]
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value. * At extreme ambient temperatures the luminaire	Lighting Technology
		LED
		Glow-wire test
		Temperature 650 °C, duration 5 s
		Flammability mark
		-
		CE mark
		Yes
		ENEC mark
		ENEC mark
		Warranty period
		5 years
		EU RoHS compliant
		No
		Embedded control
		-

Light Technical	
Upward light output ratio	0
Luminous Flux	1,008 lm
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	95 lm/W
Color rendering index (CRI)	70
Number of light sources	1
Light source color	740 neutral white
Optical cover type	Flat glass
Luminaire light beam spread	154°
Optic type outdoor	Distribution wide

Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	[DELETE] W
Average CLO power consumption	[DELETE] W
End CLO power consumption	[DELETE] W
Inrush current	15 A
Inrush time	0.36 ms
Power Consumption	11 W
Power Factor (Fraction)	0.95
Connection	Screw connection block 3-pole
Cable	-
Number of products on MCB of 16 A type B	23

Temperature	
Ambient temperature range	-40 to +50 °C

Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing	
Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Tempered glass
Fixation material	Aluminum

Housing Color	Grey
Mounting device	Diameter 76 mm adjustable
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	675 mm
Overall width	270 mm
Overall height	115 mm
Effective projected area	0.038 m²
Dimensions (Height x Width x Depth)	115 x 270 x 675 mm

Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Philips standard surge protection level
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-7%
Initial chromaticity	(0.380, 0.380) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 100000 h	L91

Application Conditions	
Performance ambient temperature Tq	25 °C

Product Data	
Order product name	BGS203 LED12/740 I DW P1 76A
Full product name	BGS203 LED12/740 I DW P1 76A
Full product code	871869631395400
Order code	910925452340
Material Nr. (12NC)	910925452340
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696313954
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696313954

Dimensional drawing

