



CoreLine Trunking

LL121X 7 WH BC

CoreLine Trunking - 7 conductors - White - Blind cover

Whether for a new facility or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Trunking range of LED products can be used to replace general lighting. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data




General Information	
Internal wiring	Standard
Connection	C-2R [Connector with 2 additional wires for light regulation]
Protection class IEC	Safety class I (I)
Glow-wire test	650/5 [Temperature 650 °C, duration 5 s]
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	CE mark
ENEC mark	-
Material	Steel
Mechanical accessories	BC [Blind cover]
Angle	-
Accessory colour	White
Product Family Code	LL121X [CoreLine Trunking]
Operating and Electrical	
Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Circuit option	7 [7 conductors]

Mechanical and Housing	
Overall length	1730 mm
Overall width	81 mm
Overall height	43 mm
Colour	White
Dimensions (height x width x depth)	43 x 81 x 1730 mm (1.7 x 3.2 x 68.1 in)
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Application Conditions	
Ambient temperature range	-20 to +35 °C
Product Data	
Full product code	871829188144500
Order product name	LL121X 7 WH BC
EAN/UPC – product	8718291881445
Order code	88144500
Numerator – quantity per pack	1

CoreLine Trunking

Numerator – packs per outer box	1
Material no. (12NC)	910925682907
Net weight (piece)	1.990 kg

Dimensional drawing



CoreLine trunking LL120X/LL121X

CoreLine trunking LL120X/LL121X

