

CoreLine Trunking

LL123X 5C6 7

CoreLine Trunking

Whether for a new facility or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Trunking range of LED products can be used to replace general lighting. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data

General Information	
Angle	-
Accessory color	White
Service tag	Yes
Product family code	LL123X [CoreLine Trunking]
ENEC mark	ENEC mark

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz


Mechanical and Housing	
Overall length	1,730 mm
Overall width	81 mm
Overall height	43 mm
Dimensions (Height x Width x Depth)	43 x 81 x 1730 mm
Material	Steel

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I

Product Data	
Order product name	LL123X 5C6 7
Full product name	LL123X 5C6 7
Full product code	871829190798500
Order code	90798500
Material Nr. (12NC)	910925683073
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291907985
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291907985

CoreLine Trunking

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.