



# Selenium

## SGP340 SON-T150W K EBD II PC D9 48/60

Selenium LED, SON-T, 150 W, Electronic regulating DALI, Safety class II, Polycarbonate bowl/cover, Universal for diameter 48 to 60 mm

Selenium SGP340 is an efficient, ergonomic road-lighting luminaire. Its simple, rounded form reduces its daytime visual impact, allowing it to integrate into any kind of environment. Selenium incorporates the renowned T-POT reflector for excellent optical performance. Energy savings are possible by means of dimming with a switch or stand-alone Chronosense system (without pilot cable). Selenium is suitable for side-entry or post-top mounting, with a choice of three tilt angles for optimal installation (0, 5, 15°).


### Product data

|                                |                                  |                                 |  |
|--------------------------------|----------------------------------|---------------------------------|--|
| <b>General Information</b>     |                                  | <b>Optic type outdoor</b>       |  |
| Lamp family code               | SON-T [SON-T]                    | Open T-POT                      |  |
| Cap-Base                       | E40 [E40]                        | <b>Operating and Electrical</b> |  |
| Gear                           | EBD [Electronic regulating DALI] | Input Voltage                   | 220 to 240 V                                 |
| Photocell                      | -                                | Power Consumption               | 150 W  |
| Product family code            | BGP340 [Selenium LED]            | <b>Mechanical and Housing</b>   |  |
| CE mark                        | Yes                              | Housing Color                   | Gray   |
| ENEC mark                      | -                                | Mounting device                 | Universal for diameter 48 to 60 mm           |
| Embedded control               | -                                | <b>Approval and Application</b> |  |
| <b>Light Technical</b>         |                                  | Ingress protection code         | IP66 [Dust penetration-protected, jet-proof] |
| Standard tilt angle posttop    | 5°                               | Mech. impact protection code    | IK10 [20 J vandal-resistant]                 |
| Standard tilt angle side entry | 0°                               | Protection class IEC            | Safety class II                              |
| Number of light sources        | 1                                |                                 |  |
| Optical cover type             | Polycarbonate bowl/cover         |                                 |  |

| Product Data        |                                       |
|---------------------|---------------------------------------|
| Order product name  | SGP340 SON-T150W K EBD II PC D9 48/60 |
| Full product name   | SGP340 SON-T150W K EBD II PC D9 48/60 |
| Full product code   | 871829105962200                       |
| Order code          | 910925720612                          |
| Material Nr. (12NC) | 910925720612                          |

|                                 |               |
|---------------------------------|---------------|
| Numerator - Quantity Per Pack   | 1             |
| EAN/UPC - Product/Case          | 8718291059622 |
| Numerator - Packs per outer box | 1             |
| EAN/UPC - Case                  | 8718291059622 |

Dimensional drawing



| Product                               |
|---------------------------------------|
| SGP340 SON-T150W K EBD II PC D9 48/60 |

