



# **Selenium**

# SGP340 SON-T250W K II PC SKD 48/60

Selenium LED, SON-T, 250 W, Safety class II, Polycarbonate bowl/cover, Universal for diameter 48 to 60 mm

Selenium SGP340 is an efficient, ergonomic road-lighting luminaire. Its simple, rounded form reduces its daytime visual impact, allowing it to integrate into any kind of environment. Selenium incorporates the renowned T-POT reflector for excellent optical performance. Energy savings are possible by means of dimming with a switch or stand-alone Chronosense system (without pilot cable). Selenium is suitable for side-entry or post-top mounting, with a choice of three tilt angles for optimal installation  $(0, 5, 15^{\circ})$ .

#### **Product data**

| General Information            |                          |
|--------------------------------|--------------------------|
| Lamp family code               | SON-T [SON-T]            |
| Cap-Base                       | E40 [E40]                |
| Gear                           | CONV [Conventional]      |
| Photocell                      | -                        |
| Product family code            | BGP340 [Selenium LED]    |
| CE mark                        | Yes                      |
| ENEC mark                      | -                        |
| Embedded control               | -                        |
|                                |                          |
| Light Technical                |                          |
| Standard tilt angle posttop    | 5°                       |
| Standard tilt angle side entry | O°                       |
| Number of light sources        | 1                        |
| Optical cover type             | Polycarbonate bowl/cover |
|                                |                          |

| Optic type outdoor           | Open T-POT                                   |
|------------------------------|--|
|                              |  |
| Operating and Electrical     |  |
| Input Voltage                | 230 to 240 V                                 |
| Power Consumption            | 250 W  |
|                              |  |
| Mechanical and Housing       |  |
| Housing Color                | Gray   |
| Mounting device              | Universal for diameter 48 to 60 mm           |
|                              |  |
| Approval and Application     |  |
| Ingress protection code      | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK08 [5 J vandal-protected]                  |
| Protection class IEC         | Safety class II                              |
|                              |  |

Datasheet, 2023, September 19 data subject to change


## **Selenium**

| Product Data        |                                    |
|---------------------|------------------------------------|
| Order product name  | SGP340 SON-T250W K II PC SKD 48/60 |
| Full product name   | SGP340 SON-T250W K II PC SKD 48/60 |
| Full product code   | 872790063567600                    |
| Order code          | 910925848112                       |
| Material Nr. (12NC) | 910925848112                       |

| Numerator - Quantity Per Pack   | 1             |
|---------------------------------|---------------|
| EAN/UPC - Product/Case          | 8727900635676 |
| Numerator - Packs per outer box | 1             |
| EAN/UPC - Case                  | 8727900635676 |
|                                 |               |


## Dimensional drawing













#### Product

SGP340 SON-T250W K II PC SKD 48/60



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.