



CoreLine Trunking

LL120X 5X2.5 WH BC

CoreLine Trunking, White

Whether for a new facility or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Trunking range of LED products can be used to replace general lighting. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data

General Information	
Angle	-
Accessory color	White
Service tag	Yes
Product family code	LL120X [CoreLine Trunking]
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Temperature	
Ambient temperature range	-20 to +35 °C
Mechanical and Housing	
Housing Color	White
Overall length	3,450 mm
Overall width	81 mm
Overall height	43 mm
Dimensions (Height x Width x Depth)	43 x 81 x 3450 mm

Material	Steel
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Product Data	
Order product name	LL120X 5X2.5 WH BC
Full product name	LL120X 5X2.5 WH BC
Full product code	871869634646400
Order code	34646400
Material Nr. (12NC)	910925863234
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696346464
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696346464