



Maxos fusion

LL512T 7 WH

Maxos fusion Rail, White

Maxos fusion is an adaptable LED trunking system that offers an excellent quality of light while more than halving energy costs compared to fluorescent lamps. For retail applications, a family of linear panels, non-linear modules and a spot portfolio can be smoothly integrated into the track backbone to let your merchandise sparkle and stand out. For industrial applications, the focus is on reducing installation and maintenance cost by using fewer linear panels. With the electrical set-up of up to 13 wires, the freedom to position these fixtures as required and the integration of other services/third-party hardware, the system allows you to reduce ceiling clutter. It can also be easily re-configured to accommodate future lay-out changes. The infrastructure is enabled to integrate sensors for data collection, giving you the opportunity to use insightful granular information to support your business.

Product data

General Information		Operating and Electrical	
Light source replaceable	No	Input Voltage	220 to 240 V
Driver included	No	Line Frequency	50 to 60 Hz
Accessory color	White	Connection	Internal connector
Product family code	LL512T [Maxos fusion Rail]	Temperature	
Value ladder	Specification	Ambient temperature range	-10 to +35 °C
CE mark	CE mark	Mechanical and Housing	
Warranty period	5 years	Fixation material	Stainless steel
Flammability mark	For mounting on normally flammable surfaces	Housing Color	White
ENEC mark	ENEC mark	Overall length	1,138 mm
Glow-wire test	Temperature 850 °C, duration 30 s	Overall width	62 mm
EU RoHS compliant	Yes	Overall height	42 mm

Maxos fusion

Dimensions (Height x Width x Depth)	42 x 62 x 1138 mm
Material	Steel
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Product Data	
Order product name	LL512T 7 WH

Full product name	LL512T 7 WH
Full product code	871869639736799
Order code	910925864257
Material Nr. (12NC)	910925864257
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696397367
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696383759

Dimensional drawing

