PHILIPS

Lighting



Libra LED

BGP630 LED35-4S/740 DM50 ALU SRG10 SI 76

LIBRA LED 65, LED module 3500 lm, 740 neutral white, Power supply unit (On/Off), Safety class I, Dust penetration-protected, jet-proof, Distribution medium 50, Aluminum, Post-top for diameter 76 mm

The elegantly styled Libra luminaire is also available in an LED version. As a fundamental element of the overall design, the bowl has been retained. Consequently, existing Libra luminaires can be retrofitted as LED fixtures by using thePhilips standerdized Ledgine O engine.

Product data

General Information	
Lamp family code	LED35 [LED module 3500 lm]
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Light source engine type	LED
Product family code	BGP630 [LIBRA LED 65]
Lighting Technology	LED
CE mark	Yes
Warranty period	5 years
Flammability mark	-
ENEC mark	-
EU RoHS compliant	No

Light Technical	
Upward light output ratio	0.4
Luminous Flux	3,150 lm
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	147 lm/W
Color rendering index (CRI)	70
Light source color	740 neutral white
Optical cover type	Polycarbonate bowl/cover clear
Luminaire light beam spread	154° - 31° x 54°
Optic type outdoor	Distribution medium 50

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	21 A

Libra LED

Inrush time	0.225 ms
Power Consumption	21.5 W
Power Factor (Fraction)	0.96
Connection	Screw connection block 3-pole
Cable	-
Number of products on MCB of 16 A type B	26

Temperature

Ambient temperature range	-40 to +50 °C

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Aluminum
Mounting device	Post-top for diameter 76 mm
Optical cover shape	Ball, globular
Optical cover finish	Clear
Overall length	773 mm
Overall width	213 mm
Overall height	183 mm
Effective projected area	0.1 m²
Dimensions (Height x Width x Depth)	183 x 213 x 773 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 10 kV differential mode and 10 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.38, 0.38) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.50 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 100000 h	L97


Application Conditions

Maximum dim level	Not applicable

Product Data

Order product name	BGP630 LED35-4S/740 DM50 ALU SRG10 SI 76
Full product name	BGP630 LED35-4S/740 DM50 ALU SRG10 SI 76
Full product code	871869638568500
Order code	910925864452
Material Nr. (12NC)	910925864452
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696385685
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696385685

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.