



CoreLine Trunking

LL121X LED76S/830 PSU WB TW3 SMB WH KIT

CoreLine Trunking, Power supply unit (On/Off), Wide beam, White

Whether for a new facility or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Trunking range of LED products can be used to replace general lighting. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data

| General Information | | ENEC mark | |
|--------------------------|--|------------------------------------|-------------------|
| Light source replaceable | No | Warranty period | 5 years |
| Number of gear units | 1 unit | EU RoHS compliant | Yes |
| Driver included | Yes | Light Technical | |
| Remarks | *-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value. | Luminous Flux | 7,600 lm |
| Service tag | Yes | Correlated Color Temperature (Nom) | 3000 K |
| Product family code | LL121X [CoreLine Trunking] | Luminous Efficacy (rated) (Nom) | 141 lm/W |
| Lighting Technology | LED | Color rendering index (CRI) | ≥80 |
| Glow-wire test | Temperature 650 °C, duration 5 s | Beam angle of light source | 120 degree(s) |
| Flammability mark | For mounting on normally flammable surfaces | Light source color | 840 neutral white |
| CE mark | Yes | Optic type | Wide beam |
| | | Luminaire light beam spread | 41° - 80° |
| | | Unified glare rating CEN | 25 |
| | | Operating and Electrical | |
| | | Input Voltage | 220 to 240 V |
| | | Line Frequency | 50 to 60 Hz |

CoreLine Trunking

| | |
|--|------------------------|
| Inrush current | 19 A |
| Inrush time | 0.28 ms |
| Power Consumption | 54 W |
| Power Factor (Fraction) | 0.97 |
| Connection | Connection unit 5-pole |
| Cable | - |
| Number of products on MCB of 16 A type B | 24 |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | -20 to +35 °C |
|---------------------------|---------------|

Controls and Dimming

| | |
|-------------------------------|----------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Constant light output | No |

Mechanical and Housing

| | |
|-------------------------------------|-------------------|
| Housing Material | Steel |
| Reflector material | - |
| Optic material | Acrylate |
| Optical cover material | Acrylate |
| Fixation material | Steel |
| Housing Color | White |
| Optical cover finish | Clear |
| Overall length | 1,730 mm |
| Overall width | 95 mm |
| Overall height | 52 mm |
| Dimensions (Height x Width x Depth) | 52 x 95 x 1730 mm |

Approval and Application

| | |
|------------------------------|-------------------------|
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |

| | |
|----------------------|----------------|
| Protection class IEC | Safety class I |
|----------------------|----------------|

Initial Performance (IEC Compliant)

| | |
|-----------------------------|--------------------------|
| Luminous flux tolerance | +/-7% |
| Initial chromaticity | (0.38, 0.38) SDCM <1t/>3 |
| Power consumption tolerance | +/-10% |

Over Time Performance (IEC Compliant)

| | |
|---|-----|
| Control gear failure rate at median useful life 50000 h | 5 % |
| Lumen maintenance at median useful life* 50000 h | L80 |

Application Conditions

| | |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C |
| Maximum dim level | Not applicable |
| Suitable for random switching | No |

Product Data

| | |
|---------------------------------|---|
| Order product name | LL121X LED76S/830 PSU WB TW3 SMB WH KIT |
| Full product name | LL121X LED76S/830 PSU WB TW3 SMB WH KIT |
| Full product code | 871869698651600 |
| Order code | 910925864629 |
| Material Nr. (12NC) | 910925864629 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8718696986516 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8718696986516 |

Dimensional drawing



