Lighting

**PHILIPS** 



# **Maxos fusion**

# LL523T 9 BK

## Maxos fusion Rail, Black

Maxos fusion is an adaptable LED trunking system that offers an excellent quality of light while more than halving energy costs compared to fluorescent lamps. For retail applications, a family of linear panels, non-linear modules and a spot portfolio can be smoothly integrated into the track backbone to let your merchandise sparkle and stand out. For industrial applications, the focus is on reducing installation and maintenance cost by using fewer linear panels. With the electrical set-up of up to 13 wires, the freedom to position these fixtures as required and the integration of other services/third-party hardware, the system allows you to reduce ceiling clutter. It can also be easily re-configured to accommodate future lay-out changes. The infrastructure is enabled to integrate sensors for data collection, giving you the opportunity to use insightful granular information to support your business.

#### **Product data**

| General Information      |   |
|--------------------------|---|
| Light source replaceable | No  |
| Driver included          | No  |
| Angle                    | -   |
| Accessory color          | Black                                       |
| Product family code      | LL523T [Maxos fusion Rail]                  |
| Value ladder             | Specification                               |
| CE mark                  | CE mark                                     |
| Warranty period          | 5 years                                     |
| Flammability mark        | For mounting on normally flammable surfaces |
| ENEC mark                | ENEC mark                                   |
| Glow-wire test           | Temperature 850 °C, duration 30 s           |
| EU RoHS compliant        | Yes   |

| Operating and Electrical  |                    |
|---------------------------|--------------------|
| Input Voltage             | 220 to 230 V       |
| Line Frequency            | 50 to 60 Hz        |
| Connection                | Internal connector |
|                           |                    |
| Temperature               |                    |
| Ambient temperature range | -10 to +35 °C      |
|                           |                    |
| Mechanical and Housing    |                    |
| Fixation material         | Stainless steel    |
| Housing Color             | Black              |
| Overall length            | 2,276 mm           |
| Overall width             | 62 mm              |
| Overall height            | 42 mm              |
|                           |                    |

# **Maxos fusion**

| 42 x 62 x 2276 mm       |
|-------------------------|
| Steel                   |
|                         |
|                         |
| IP20 [Finger-protected] |
| IK02 [0.2 J standard]   |
| Safety class I          |
|                         |
|                         |
| LL523T 9 BK             |
|                         |

| Full product name               | LL523T 9 BK     |
|---------------------------------|-----------------|
| Full product code               | 871869943454099 |
| Order code                      | 43454099        |
| Material Nr. (12NC)             | 910925864655    |
| Numerator - Quantity Per Pack   | 1               |
| EAN/UPC - Product/Case          | 8718699434540   |
| Numerator - Packs per outer box | 10              |
| EAN/UPC - Case                  | 8718696986776   |
|                                 |                 |

### Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, August 3 - data subject to change