



CoreLine recessed

RC134B LED27S/840 PSD W60L60 ELB3 OC

CoreLine recessed, 25.5 W, 600x600 mm, 2700 lm, 4000 K, DALI, UGR19, ELB3h

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Recessed range of LED products can be used to replace functional luminaires in general lighting applications. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that The environment in which The luminaire is to be installed is suitably checked
- If the above advice is not taken and the luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

Product data

| General Information | | Lighting Technology | |
|--------------------------|--|---------------------|---|
| Light source replaceable | No | Value ladder | Performance |
| Number of gear units | 1 unit | CE mark | Yes |
| Driver included | Yes | Warranty period | 5 years |
| Remarks | *-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value. | Flammability mark | For mounting on normally flammable surfaces |
| Service tag | Yes | ENEC mark | ENEC mark |
| Product family code | RC134B [Coreline Recessed] | Glow-wire test | Temperature 850 °C, duration 30 s |
| | | EU RoHS compliant | Yes |
| | | Light Technical | |
| | | Luminous Flux | 2,700 lm |

CoreLine recessed

| | |
|------------------------------------|-------------------|
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 106 lm/W |
| Color rendering index (CRI) | ≥80 |
| Light source color | 840 neutral white |
| Optic type | Wide beam |
| Luminaire light beam spread | 81° |
| Unified glare rating CEN | 22 |

Operating and Electrical

| | |
|--|-----------------------------------|
| Input Voltage | 220-240 V |
| Line Frequency | 50 to 60 Hz |
| Inrush current | 14.7 A |
| Inrush time | 0.25 ms |
| Power Consumption | 25.5 W |
| Power Factor (Fraction) | 0.9 |
| Connection | Push-in connector and pull relief |
| Cable | - |
| Number of products on MCB of 16 A type B | 38 |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | +10 to +40 °C |
|---------------------------|---------------|

Controls and Dimming

| | |
|-------------------------------|---------------------------------------|
| Dimmable | Yes |
| Driver/power unit/transformer | Power supply unit with DALI interface |
| Control interface | DALI |
| Constant light output | No |

Mechanical and Housing

| | |
|------------------------|---------------|
| Housing Material | Steel |
| Reflector material | Polycarbonate |
| Optic material | Polycarbonate |
| Optical cover material | Polycarbonate |
| Fixation material | - |
| Housing Color | White |
| Optical cover finish | Textured |
| Overall length | 597 mm |

| | |
|-------------------------------------|-------------------|
| Overall width | 597 mm |
| Overall height | 41 mm |
| Dimensions (Height x Width x Depth) | 41 x 597 x 597 mm |

Approval and Application

| | |
|------------------------------|-------------------------------------|
| Ingress protection code | IP44 [Wire-protected, splash-proof] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| Sustainability rating | - |
| Protection class IEC | Safety class I |

Initial Performance (IEC Compliant)

| | |
|-----------------------------|----------------------|
| Luminous flux tolerance | +/-8% |
| Initial chromaticity | (0.38, 0.38) SDCM <3 |
| Power consumption tolerance | +/-10% |

Over Time Performance (IEC Compliant)

| | |
|---|-----|
| Control gear failure rate at median useful life 50000 h | 5 % |
| Lumen maintenance at median useful life* 50000 h | L75 |


Application Conditions

| | |
|------------------------------------|-----------------------------------|
| Performance ambient temperature Tq | 25 °C |
| Maximum dim level | 1% (no dimming in emergency mode) |
| Suitable for random switching | Yes |

Product Data

| | |
|---------------------------------|--------------------------------------|
| Order product name | RC134B LED27S/840 PSD W60L60 ELB3 OC |
| Full product name | RC134B LED27S/840 PSD W60L60 ELB3 OC |
| Full product code | 871869934822900 |
| Order code | 34822900 |
| Material Nr. (12NC) | 910925864780 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8718699348229 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8718699348229 |

Dimensional drawing



CoreLine recessed

