



# CoreLine recessed

## RC134B LED37S/830 W30L120 IA1 OC

CoreLine recessed, 35.4 W, 1200x300 mm, 3700 lm, 3000 K, Wireless, Interact Ready, UGR19

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Recessed range of LED products can be used to replace functional luminaires in general lighting applications. The process of selecting, installing and maintaining is so easy – it's a simple switch.

### Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that The environment in which The luminaire is to be installed is suitably checked
- If the above advice is not taken and the luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

### Product data

General Information		Flammability mark	
Light source replaceable	No		For mounting on normally flammable surfaces
Number of gear units	1 unit	ENEC mark	ENEC mark
Driver included	Yes	Glow-wire test	Temperature 850 °C, duration 30 s
Service tag	Yes	EU RoHS compliant	Yes
Product family code	RC134B [Coreline Recessed]	Light Technical	
Connectivity	Interact Ready	Luminous Flux	3,700 lm
Lighting Technology	LED	Correlated Color Temperature (Nom)	3000 K
Value ladder	Performance	Luminous Efficacy (rated) (Nom)	104.5 lm/W
Embedded control	Interact SNS210 sensor	Color rendering index (CRI)	≥80
CE mark	Yes	Light source color	830 warm white
Warranty period	5 years		

## CoreLine recessed

Optic type	Wide beam
Luminaire light beam spread	81°
Unified glare rating CEN	19

### Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	22 A
Inrush time	0.275 ms
Power Consumption	35.4 W
Power Factor (Fraction)	0.9
Connection	Push-in connector and pull relief
Cable	-
Number of products on MCB of 16 A type B	24

### Temperature

Ambient temperature range	+10 to +40 °C
---------------------------	---------------

### Controls and Dimming

Dimmable	Wireless Dim
Driver/power unit/transformer	Power supply unit regulating external
Control interface	Wireless
Constant light output	No

### Mechanical and Housing

Housing Material	Steel
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover finish	Textured
Overall length	1,197 mm
Overall width	297 mm
Overall height	41 mm
Dimensions (Height x Width x Depth)	41 x 297 x 1197 mm

### Approval and Application

Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class I

### Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-8%
Initial chromaticity	(0.43, 0.40) SDCM <3
Power consumption tolerance	+/-10%

### Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	1 %
Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L75


### Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	1%
Suitable for random switching	Yes

### Product Data

Order product name	RC134B LED37S/830 W30L120 IA1 OC
Full product name	RC134B LED37S/830 W30L120 IA1 OC
Full product code	871869699656000
Order code	99656000
Material Nr. (12NC)	910925865177
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696996560
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696996560

## Dimensional drawing



CoreLine recessed

