



# CoreLine Recessed

## RC134B LED37S/830 W30L120 IA1 NOC

Coreline Recessed - 830 warm white - Power supply unit regulating external (PSR)

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Recessed range of LED products can be used to replace functional luminaires in general lighting applications. The process of selecting, installing and maintaining is so easy – it's a simple switch.

### Product data

General Information		Warranty period	
Light source colour	830 warm white	Warranty period	5 years
Light source replaceable	No	Constant light output	No
Number of gear units	1 unit	Number of products on MCB	24
Driver/power unit/transformer	PSR-E [ Power supply unit regulating external (PSR)]	RoHS mark	RoHS mark
Driver included	Yes	Product Family Code	RC134B [ Coreline Recessed]
Optic type	WB [ Wide beam]	Unified glare rating CEN	22
Luminaire light beam spread	93°	Operating and Electrical	
Connection	PIP [ Push-in connector and pull relief]	Input voltage	220-240 V
Cable	-	Input frequency	50 to 60 Hz
Protection class IEC	Safety class I (I)	Inrush current	22 A
Glow-wire test	850/30 [ Temperature 850 °C, duration 30 s]	Inrush time	0.275 ms
Flammability mark	F [ For mounting on normally flammable surfaces]	Power factor (min.)	0.9
CE mark	CE mark	Mechanical and Housing	
ENEC mark	ENEC mark	Housing material	Steel
		Reflector material	Polycarbonate
		Optic material	Polycarbonate

## CoreLine Recessed

Optical cover/lens material	Polycarbonate
Fixation material	-
Optical cover/lens finish	Textured
Overall length	1197 mm
Overall width	297 mm
Overall height	41 mm
Colour	White

### Approval and Application

Ingress protection code	IP20/44 [ Finger-protected; wire-protected, splash-proof]
Mech. impact protection code	IK02 [ 0.2 J standard]

### Initial Performance (IEC Compliant)

Initial luminous flux	3700 lm
Luminous flux tolerance	+/-8%
Initial LED luminaire efficacy	104.5 lm/W
Init. Corr. colour temperature	3000 K
Init. colour rendering index	≥80
Initial chromaticity	(0.43, 0.40) SDCM <3
Initial input power	35.4 W
Power consumption tolerance	+/-10%

### Over Time Performance (IEC Compliant)


Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L75

### Application Conditions


Ambient temperature range	+10 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	1%

### Product Data

Full product code	871869699657700
Order product name	RC134B LED37S/830 W30L120 IA1 NOC
EAN/UPC – product	8718696996577
Order code	99657700
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910925865178
Net weight (piece)	3.000 kg



## Dimensional drawing



### CoreLine Recessed RC134B/RC135B

