



Iridium gen3 LED Medium

BGP382 GRN55/740 I DM CO GR SP

Iridium gen3 Medium, LED GreenLine 5500 lm, 740 neutral white, Safety class I, Distribution medium, Grey, Philips standard surge protection level, Spigot

Iridium gen3 is the first truly intelligent luminaire designed for seamless connectivity. No hassle in commissioning – just install the luminaire and control it from a distance through CityTouch management software. Remote light management made easy! The new ‘plug & play’ concept has been designed to ensure safe and easy installation in just three steps: 1. Install the spigot, 2. Plug in the mains, 3. Tilt and close the luminaire. The luminaire’s high efficiency at system level ensures significant energy savings compared to existing conventional installations, offering a fast payback. Thanks to its wide choice of lumen packages, optics and color temperatures, Iridium gen3 fits most applications in residential areas. The luminaire’s neo-classical design guarantees a consistent look and feel for your surroundings.

Product data

| General Information | | |
|--------------------------|--|--|
| Lamp family code | GRN55 [LED GreenLine 5500 lm] | B10. Therefore, the median useful life (B50) value also represents the B10 value. * At extreme ambient temperatures the luminaire might automatically dim down to protect components |
| Light source replaceable | Yes | |
| Number of gear units | 1 unit | |
| Driver included | Yes | |
| Remarks | *-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example | Light source engine type |
| | | LED |
| | | Product family code |
| | | BGP382 [Iridium gen3 Medium] |
| | | Lighting Technology |
| | | LED |
| | | Flammability mark |
| | | - |
| | | CE mark |
| | | Yes |

Iridium gen3 LED Medium

| | |
|-------------------|-----------|
| ENEC mark | ENEC mark |
| Warranty period | 5 years |
| EU RoHS compliant | No |

Light Technical

| | |
|------------------------------------|--------------------------|
| Upward light output ratio | 0 |
| Luminous Flux | 5,208 lm |
| Standard tilt angle posttop | 0° |
| Standard tilt angle side entry | 0° |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 155 lm/W |
| Color rendering index (CRI) | 70 |
| Light source color | 740 neutral white |
| Optical cover type | Polycarbonate bowl/cover |
| Luminaire light beam spread | 152° |
| Optic type outdoor | Distribution medium |

Operating and Electrical

| | |
|--|-------------------------------|
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 to 60 Hz |
| Initial CLO power consumption | [delete] W |
| Average CLO power consumption | [delete] W |
| End CLO power consumption | [delete] W |
| Inrush current | 45 A |
| Inrush time | 0.285 ms |
| Power Consumption | 33.5 W |
| Power Factor (Fraction) | 0.94 |
| Connection | Screw connection block 3-pole |
| Cable | - |
| Number of products on MCB of 16 A type B | 10 |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Controls and Dimming

| | |
|-------------------------------|------------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit regulating |
| Control interface | - |
| Constant light output | No |

Mechanical and Housing

| | |
|--------------------|---------------|
| Housing Material | Aluminum |
| Reflector material | - |
| Optic material | Polycarbonate |

| | |
|-------------------------------------|----------------------|
| Optical cover material | Polycarbonate |
| Fixation material | Aluminum |
| Housing Color | Grey |
| Mounting device | Spigot |
| Optical cover shape | Flat |
| Optical cover finish | Textured |
| Overall length | 650 mm |
| Overall width | 330 mm |
| Overall height | 157 mm |
| Effective projected area | 0.031 m ² |
| Dimensions (Height x Width x Depth) | 157 x 330 x 650 mm |

Approval and Application

| | |
|--|--|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK09 [10 J] |
| Surge Protection (Common/Differential) | Philips standard surge protection level |
| Protection class IEC | Safety class I |

Initial Performance (IEC Compliant)

| | |
|---------------------------------------|----------------------|
| Luminous flux tolerance | +/-7% |
| Initial chromaticity | (0.38, 0.38) SDCM <5 |
| Power consumption tolerance | +/-10% |
| Init. Color Rendering Index Tolerance | +/-2 |

Over Time Performance (IEC Compliant)

| | |
|--|------|
| Control gear failure rate at median useful life 100000 h | 10 % |
| Lumen maintenance at median useful life* 100000 h | L80 |

Application Conditions

| | |
|------------------------------------|-------|
| Performance ambient temperature Tq | 25 °C |
|------------------------------------|-------|

Product Data

| | |
|---------------------------------|--------------------------------|
| Order product name | BGP382 GRN55/740 I DM CO GR SP |
| Full product name | BGP382 GRN55/740 I DM CO GR SP |
| Full product code | 871869699734500 |
| Order code | 910925865256 |
| Material Nr. (12NC) | 910925865256 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8718696997345 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8718696997345 |

Iridium gen3 LED Medium

Dimensional drawing

