



CoreLine panel

RC125Z SME-2 WH

Accessory, White, 0.2 J standard, Finger-protected

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Panel range of LED products can be used to replace functional luminaires in general lighting applications. Both Non-Office Compliant (NOC) version and Office Compliant version (OC) are now available. The process of selecting, installing and maintaining is so easy – it's a simple switch. Also available as an Interact Ready wireless CoreLine luminaire panel that works with Interact Pro lighting software and InteractReady devices to provide a connected lighting system for SMEs

Product data

General Information	
Accessory colour	White
Value ladder	Performance
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Mechanical and Housing	
Overall length	1,500 mm
Overall height	30 mm
Overall diameter	92 mm
Material	Composite
Approval and Application	
Ingress protection code	IP20 [Finger-protected]

Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II
Product Data	
Order product name	RC125Z SME-2 WH
Full product name	RC125Z SME-2 WH
Full EOC	871869607334699
Order code	07334699
Material no. (12 NC)	910930031418
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8718696073346
Numerator – packs per outer box	20
EAN/UPC - Case	8718696073407