



ConTempo 150-250-350

RVP350 L 1xHPI-T/SON-T 250/400W SY

1, Empty, without gear, Symmetrical

The Contempo floodlight has a registered design that blends well with contemporary outdoor environments. It has a rugged pressure die-casted aluminum housing with corrosion resistant powder coating. Contempo also features an integrated energy saving copper ballast, electronic semi-parallel ignitor and capacitor. The unit has passed rigorous tests for dust and water ingress protection.

Product data

General Information	
Lamp family code	-
Gear	E [Empty, without gear]
Light Technical	
Number of light sources	1
Optic type outdoor	Symmetrical
Operating and Electrical	
Input Voltage	220 V
Line Frequency	50 Hz
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]

Product Data	
Order product name	RVP350 L 1xHPI-T/SON-T 250/400W SY
Full product name	RVP350 L 1xHPI-T/SON-T 250/400W SY
Full product code	911401041780
Order code	911401041780
Material Nr. (12NC)	911401041780
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828621582
Numerator - Packs per outer box	1
EAN/UPC - Case	6923828621582

ConTempo 150-250-350

Dimensional drawing

