

ConTempo 150-250-350

RVP350 SON-T250W IC 220V-50Hz A SP

SON-T, 250 W, Asymmetrical

The Contempo floodlight has a registered design that blends well with contemporary outdoor environments. It has a rugged pressure die-casted aluminum housing with corrosion resistant powder coating. Contempo also features an integrated energy saving copper ballast, electronic semi-parallel ignitor and capacitor. The unit has passed rigorous tests for dust and water ingress protection.

Product data

General Information	
Lamp family code	SON-T [SON-T]
Cap-Base	E40 [E40]
Gear	CONV [Conventional]

Light Technical	
Number of light sources	1
Optic type outdoor	Asymmetrical


Operating and Electrical	
Input Voltage	220 V
Line Frequency	50 Hz
Power Consumption	250 W

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]

Product Data	
Order product name	RVP350 SON-T250W IC 220V-50Hz A SP
Full product name	RVP350 SON-T250W IC 220V-50Hz A SP
Full product code	911401042980
Order code	911401042980
Material Nr. (12NC)	911401042980
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828620325
Numerator - Packs per outer box	1
EAN/UPC - Case	6923828620325

ConTempo 150-250-350

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.