

Greenperform Waterproof G2 - WT188C

WT168C LED40 CW L1200 PSU

Greenperform Waterproof G2 - WT188C, 34 W, 4000 lm, 6500 K, 120°

Greenperform Waterproof G2 luminaire and its components are designed for both indoor and semi-outdoor application (anti-UV PC material housing and diffuser, stainless steel installation accessory). We design for friendly optical, energy saving, reliable quality, and easy wiring. Beyond that, GreenParking wireless motion detective system is ready to provide the maximum energy saving and new lighting experience to you.

Product data

General Information		Correlated Color Temperature (Nom)		6500 K
Light source replaceable	No	Luminous Efficacy (rated) (Nom)	117 lm/W	
Number of gear units	1 unit	Color rendering index (CRI)	>80	
Driver included	Yes	Light source color	865 cool daylight	
Light source engine type	LED	Optic type	Symmetrical	
Glow-wire test	Temperature 750 °C, duration 5 s	Optical cover type	Polycarbonate bowl/cover foggy	
CE mark	CE mark	Luminaire light beam spread	120°	
Warranty period	3 years			
EU RoHS compliant	Yes			
Light Technical		Operating and Electrical		
Luminous Flux	4,000 lm	Input Voltage	220 to 240 V	
		Line Frequency	50 to 60 Hz	
		Inrush current	12 A	

Greenperform Waterproof G2 - WT188C

Inrush time	0.59 ms
Power Consumption	34 W
Power Factor (Fraction)	0.9
Connection	Screw connection block
Number of products on MCB of 16 A type B	24

Temperature

Ambient temperature range	-30 to +45 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Steel
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Gray and white
Optical cover finish	Opal
Overall length	1,183 mm
Overall width	84 mm
Overall height	83 mm
Dimensions (Height x Width x Depth)	83 x 84 x 1183 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	SDCM<5
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Median useful life L70B50	50,000 hour(s)
Median useful life L80B50	45,000 hour(s)
Median useful life L90B50	35,000 hour(s)


Application Conditions

Maximum dim level	Not applicable
-------------------	----------------

Product Data

Order product name	WT168C LED40 CW L1200 PSU
Full product name	WT168C LED40 CW L1200 PSU
Full product code	911401511941
Order code	911401511941
Material Nr. (12NC)	911401511941
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing



Greenperform Waterproof G2 - WT188C

